

# Safety Data Sheet prepared to UN GHS Revision 3

# 1. Identification of the Substance/Mixture and the Company/Undertaking

1.1	Product Identifier	0525S1NL		
	Product Name:	THINNER 25	Revision Date:	06/18/2015
1.2	Relevant identified uses of the substance or mixture and uses advised against	Thinner for industrial coatings - Industrial use	Supercedes Date:	05/30/2015
1.3	Details of the supplier of the safety	data sheet		
	Manufacturer:	Carboline Company 2150 Schuetz Road St. Louis, MO USA 63146 Regulatory / Technical Information: Contact Carboline Technical Services at 1-800-848-4645		
	Datasheet Produced by:	Schlereth, Ken - ehs@stoncor.com		
1.4	Emergency telephone number:	CHEMTREC 1-800-424-9300 (Inside US) CHEMTREC +1 703 5273887 (Outside US) HEALTH - Pittsburgh Poison Control 1-412-681-6669		

# 2. Hazard Identification

#### 2.1 Classification of the substance or mixture

Hazardous to the aquatic environment, Chronic, category 3 Eye Irritation, category 2 Flammable Liquid, category 3 STOT, repeated exposure, category 2 STOT, single exposure, category 3, RTI Skin Irritation, category 2

## 2.2 Label elements

### Symbol(s) of Product



Signal Word

Warning

# Named Chemicals on Label

1,2,4 TRIMETHYLBENZENE, CUMENE, ETHYL BENZENE, 1,3,5-TRIMETHYLBENZENE, XYLENE, TRIMETHYLBENZENE

### GHS HAZARD STATEMENTS

Flammable Liquid, category 3 Skin Irritation, category 2 Eye Irritation, category 2 STOT, single exposure, category 3, RTI STOT, repeated exposure, category 2 Hazardous to the aquatic environment,	H226 H315 H319 H335 H373 H412	Flammable liquid and vapour. Causes skin irritation. Causes serious eye irritation. May cause respiratory irritation. May cause damage to organs through prolonged or repeated exposure. Harmful to aquatic life with long lasting effects.
Chronic, category 3		harman to aquatio no mariong lacting crocio.
GHS PRECAUTION PHRASES		
	P210	Keep away from heat/sparks/open flames/hot surfaces No smoking.
	P260	Do not breathe dust/fume/gas/mist/vapours/spray.
	P273	Avoid release to the environment.
	P280	Wear protective gloves/protective clothing/eye protection/ face protection.
	P304+340	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
	P305+351+338	F IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do so. Continue rinsing.
	P314	Get medical advice/attention if you feel unwell.
	P332+313	If skin irritation occurs: Get medical advice/attention.
	P403+233	Store in a well-ventilated place. Keep container tightly closed.

#### 2.3 Other hazards

Not applicable

## Results of PBT and vPvB assessment:

The product does not meet the criteria for PBT/VPvB in accordance with Annex XIII.

# 3. Composition/Information On Ingredients

### 3.2 Mixtures

#### Hazardous Ingredients

CAS-No.	Chemical Name	<u>%</u>
1330-20-7	XYLENE	25-50
108-65-6	1-METHOXY-2-PROPANOL ACETATE	10-25
64742-95-6	AROMATIC HYDROCARBON	10-25
100-41-4	ETHYL BENZENE	10-25
95-63-6	1,2,4 TRIMETHYLBENZENE	2.5-10

Ď

98-82-8 25551-13-7 108-67-8	CUMENE TRIMETHYLBENZENE 1,3,5-TRIMETHYLBENZENE		2.5-10 2.5-10 2.5-10
CAS-No.	GHS Symbols	GHS Hazard Statements	M-Factors
1330-20-7	GHS02-GHS07	H226-312-315-319-332-335	0
108-65-6	GHS02	H226	0
64742-95-6	GHS02-GHS08-GHS09	H226-411	0
100-41-4	GHS02-GHS07-GHS08	H225-332-373-412	0
98-82-8	GHS02-GHS07-GHS08-GHS09	H226-335-411	0
95-63-6	GHS02-GHS07-GHS09	H226-315-319-332-335-411	0
108-67-8	GHS02-GHS07	H226-335	0

The text for GHS Hazard Statements shown above (if any) is given in Section 16.

H226-315-319-332-335-336-411

## 4. First-aid Measures

Additional Information:

25551-13-7

#### 4.1 Description of First Aid Measures

GHS02-GHS07-GHS09

**AFTER INHALATION:** Give oxygen or artificial respiration if needed. Remove person to fresh air. If signs/symptoms continue, get medical attention.

**AFTER SKIN CONTACT:** In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. If skin irritation persists, call a physician.

AFTER EYE CONTACT: Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician.

**AFTER INGESTION:** Do NOT induce vomiting. Never give anything by mouth to an unconscious person. If swallowed, call a poison control centre or doctor immediately.

#### 4.2 Most important symptoms and effects, both acute and delayed

Harmful if swallowed. Irritating to eyes and skin. Risk of serious damage to the lungs (by aspiration). Vapours may cause drowsiness and dizziness.

#### 4.3 Indication of any immediate medical attention and special treatment needed

No information available on clinical testing and medical monitoring. Specific toxicological information on substances, if available, can be found in section 11.

# 5. Fire-fighting Measures

### 5.1 Extinguishing Media:

Carbon Dioxide, Dry Chemical, Foam, Water Fog

**UNUSUAL FIRE AND EXPLOSION HAZARDS:** Flammable liquid. Vapours are heavier than air and may spread along floors. Vapours may form explosive mixtures with air. Vapors may travel to areas away from work site before igniting/flashing back to vapor source. Provide adequate ventilation. Prevent the creation of flammable or explosive concentrations of vapour in air and avoid vapour concentration higher than the occupational exposure limits. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Electrical installations / working materials must comply with the technological safety standards. Wear shoes with conductive soles.

#### 5.2 Special hazards arising from the substance or mixture

No Information

#### 5.3 Advice for firefighters

In the event of fire, wear self-contained breathing apparatus. Cool containers / tanks with water spray. Flammable.

# 6. Accidental Release Measures

## 6.1 Personal precautions, protective equipment and emergency procedures

For personal protection see section 8. Ensure adequate ventilation. Ensure adequate ventilation. Evacuate personnel to safe areas. Evacuate personnel to safe areas. Remove all sources of ignition. Remove all sources of ignition. To avoid ignition of vapours by static electricity discharge, all metal parts of the equipment must be grounded. Wear personal protective equipment.

#### 6.2 Environmental precautions

Do not allow material to contaminate ground water system. Prevent product from entering drains.

### 6.3 Methods and material for containment and cleaning up

Contain spillage, soak up with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and transfer to a container for disposal according to local / national regulations (see section 13). Contain spillage, soak up with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and transfer to a container for disposal according to local / national regulations (see section 13).

### 6.4 Reference to other sections

Please refer to disposal requirements or country specific disposal requirements for this material. See Section 13 for further information.

# 7. Handling and Storage

## 7.1 Precautions for safe handling

**INSTRUCTIONS FOR SAFE HANDLING :** Keep containers dry and tightly closed to avoid moisture absorption and contamination. Prepare the working solution as given on the label(s) and/or the user instructions. Do not breathe vapours or spray mist. Ensure all equipment is electrically grounded before beginning transfer operations. Do not use sparking tools. Wash thoroughly after handling. Do not get in eyes, on skin, or on clothing. Use only with adequate ventilation/personal protection.

**PROTECTION AND HYGIENE MEASURES :** Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday. When using, do not eat, drink or smoke.

#### 7.2 Conditions for safe storage, including any incompatibilities

#### CONDITIONS TO AVOID: Heat, flames and sparks.

**STORAGE CONDITIONS:** Keep container closed when not in use. Store in a dry, well ventilated place away from sources of heat, ignition and direct sunlight.

#### 7.3 Specific end use(s)

No specific advice for end use available.

## 8. Exposure Controls/Personal Protection

### 8.1 Control parameters

### Ingredients with Occupational Exposure Limits

(US)

<u>Name</u>	<u>%</u>	<u>ACGIH TLV-</u> TWA	<u>ACGIH TLV-</u> STEL	<u>osha pel-</u> Twa	<u>osha pel-</u> Ceiling	OEL Note
XYLENE	25-50	100 PPM	150 PPM	435 MGM3	N/E	
1-METHOXY-2-PROPANOL ACETATE	10-25	N/E	N/E	N/E	N/E	
AROMATIC HYDROCARBON	10-25	N/E	N/E	N/E	N/E	
ETHYL BENZENE	10-25	20 PPM	N/E	435 MGM3	N/E	
1,2,4 TRIMETHYLBENZENE	2.5-10	25 PPM	N/E	125 MGM3	N/E	
CUMENE	2.5-10	50 PPM	N/E	245 MG/M3	N/E	
TRIMETHYLBENZENE	2.5-10	25 PPM	N/E	125 MGM3	N/E	
1,3,5-TRIMETHYLBENZENE	2.5-10	25 PPM	N/E	125 MGM3	N/E	

FURTHER INFORMATION: Refer to the regulatory exposure limits for the workforce enforced in each country.

#### 8.2 Exposure controls

#### **Personal Protection**

**RESPIRATORY PROTECTION:** In order to avoid inhalation of spray-mist and sanding dust, all spraying and sanding must be done wearing adequate respirator. Use only with ventilation to keep levels below exposure guidelines reported in this

document. User should test and monitor exposure levels to ensure all personnel are below guidelines. If not sure, or not able to monitor, use State or federally approved supplied air respirator. For silica containing coatings in a liquid state, and/or if no exposure limits are established above, air-supplied respirators are generally not required.

## EYE PROTECTION: Safety glasses with side-shields.

**HAND PROTECTION:** Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough. Impervious glovesRequest information on glove permeation properties from the glove supplier.

**OTHER PROTECTIVE EQUIPMENT:** Ensure that eyewash stations and safety showers are close to the workstation location. Lightweight protective clothing

**ENGINEERING CONTROLS:** Avoid contact with skin, eyes and clothing. Ensure adequate ventilation, especially in confined areas.

# 9. Physical and Chemical Properties

9.1	Information on basic physical and chemical properties	
	Appearance:	Clear Liquid
	Physical State	Liquid
	Odor	Ester
	Odor threshold	N/D
	рН	N/D
	Melting point / freezing point (°C)	N/D
	Boiling point/range (°C)	284 F (140C) - 334 F (168 C)
	Flash Point, (°C)	27
	Evaporation rate	Slower Than Ether
	Flammability (solid, gas)	Not determined
	Upper/lower flammability or explosive limits	1.2 - 7.1
	Vapour Pressure, mmHg	4.5 mmHg @ 20C
	Vapour density	Heavier than Air
	Relative density	Not determined
	Solubility in / Miscibility with water	N/D
	Partition coefficient: n-octanol/water	Not determined
	Auto-ignition temperature (°C)	Not determined
	Decomposition temperature (°C)	Not determined
	Viscosity	Unknown
	Explosive properties	Not determined
	Oxidising properties	Not determined
9.2	Other information	
	VOC Content g/l:	892
	Specific Gravity (g/cm3)	0.89

# 10. Stability and Reactivity

10.1 Reactivity

No reactivity hazards known under normal storage and use conditions.

#### 10.2 Chemical stability

Stable under normal conditions.

#### 10.3 Possibility of hazardous reactions

Hazardous polymerisation does not occur.

### 10.4 Conditions to avoid

Heat, flames and sparks.

### 10.5 Incompatible materials

Strong oxidizing agents.

### 10.6 Hazardous decomposition products

Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), dense black smoke.

11.	11. Toxicological Information				
11.1	Information on toxicological effects				
Acute Toxicity:					
	Oral LD50:	N/D			
	Inhalation LC50:	N/D			
	Irritation:	Unknown			
	Corrosivity:	Unknown			
	Sensitization:	Unknown			
	Repeated dose toxicity:	Unknown			
	Carcinogenicity:	Unknown			
	Mutagenicity:	Unknown			

Toxicity for reproduction: Unknown

If no information is available above under Acute Toxicity then the acute effects of this product have not been tested. Data on individual components are tabulated below:

CAS-No.	Chemical Name	Oral LD50	Dermal LD50	Vapor LC50
1330-20-7	XYLENE	4300 mg/kg, rat, oral		15000 ppm/4 hrs rat, inhalation
108-65-6	1-METHOXY-2-PROPANOL ACETATE	8532 mg/kg, oral (rat)	>5000 mg/kg	101 ppm/4 hr, rat, inh
64742-95-6	AROMATIC HYDROCARBON	4700 mg/kg, oral, rat		3670 ppm/8 hours, rat, inhalation
100-41-4	ETHYL BENZENE	3500 mg/kg rat, oral	>5000 mg/l, dermal rabbit	17.2 mg/L Inh, Rat, 4Hr
98-82-8	CUMENE	2910 mg/kg, oral, rat	12300 MG/KG (RABBIT)	8000 ppm / 4 hours
95-63-6	1,2,4 TRIMETHYLBENZENE	6000 mg/kg, oral, rat		18000 mg / m3 / 4 hours
108-67-8	1,3,5-TRIMETHYLBENZENE	Not Available		Not Available

#### 25551-13-7 TRIMETHYLBENZENE

NE

Product: 0525S1NL

NE

#### Additional Information:

Harmful if swallowed. Irritating to eyes and skin. Risk of serious damage to the lungs (by aspiration). Vapours may cause drowsiness and dizziness.

	city: C50 48hr (Daphnia):			
	C50 48hr (Daphnia):			
		Unknown		
IC	C50 72hr (Algae):	Unknown		
L	C50 96hr (fish):	Unknown		
12.2 Pers	istence and degradability:	Unknown		
12.3 Bioa	ccumulative potential:	Unknown		
12.4 Mob	ility in soil:	Unknown		
	ults of PBT and vPvB essment:	The product does n	ot meet the criteria for F	PBT/VPvB in accordance with Annex XII
12.6 Othe	er adverse effects:	Unknown		
CAS-No.	Chemical Name	<u>EC50 48hr</u>	<u>IC50 72hr</u>	LC50 96hr
1330-20-7	XYLENE	No information	on No informatio	on No information
108-65-6	1-METHOXY-2-PROPANOL ACETAT	E No information	on No informatio	on No information
64742-95-6	AROMATIC HYDROCARBON	No information	on No informatio	on No information
100-41-4	ETHYL BENZENE	No information	on No informatio	on No information
95-63-6	1,2,4 TRIMETHYLBENZENE	No information	on No informatio	on No information
98-82-8	CUMENE	No information	on No informatio	on 6/32 mg/l (Fish)
25551-13-7	TRIMETHYLBENZENE	No information	on No informatio	on No information
108-67-8	1,3,5-TRIMETHYLBENZENE	No information	on No informatio	on No information

# 13. Disposal Considerations

**13.1** WASTE TREATMENT METHODS: Do not burn, or use a cutting torch on, the empty drum. If recycling is not practicable, dispose of in compliance with local regulations. Dispose of in accordance with local regulations. Empty containers should be taken to an approved waste handling site for recycling or disposal.

## 14. Transport Information

14.1	UN number	UN 1263
14.2	UN proper shipping name	Paint Related Material
	Technical name	N/A
14.3	Transport hazard class(es)	3
	Subsidiary shipping hazard	N/A
14.4	Packing group	III
14.5	Environmental hazards	Unknown
14.6	Special precautions for user	Unknown
	EmS-No.:	F-E, S-E
14.7	Transport in bulk according to Annex II of MARPOL 73/78 and the IBC code	Unknown

# 15. Regulatory Information

15.1 Safety, health and environmental regulations/legislation for the substance or mixture:

# U.S. Federal Regulations: As follows -

## **CERCLA - Sara Hazard Category**

This product has been reviewed according to the EPA 'Hazard Categories' promulgated under Sections 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:

Fire Hazard, Acute Health Hazard, Chronic Health Hazard

#### Sara Section 313:

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendment and Reauthorization Act of 1986 and 40 CFR part 372:

Chemical Name	CAS-No.
XYLENE	1330-20-7
ETHYL BENZENE	100-41-4
CUMENE	98-82-8
1,2,4 TRIMETHYLBENZENE	95-63-6

#### **Toxic Substances Control Act:**

This product contains the following chemical substances subject to the reporting requirements of TSCA 12(B) if exported from the United States:

No TSCA 12(b) components exist in this product.

#### U.S. Clean Air Act:

EPA Coating Category: EPA VOC Content Limit (g/l): Product VOC Content (g/l) Thinning Recommendations: Application Recommendations:

Harmful if swallowed.

# U.S. State Regulations: As follows -

### New Jersey Right-to-Know:

The following materials are non-hazardous, but are among the top five components in this product.

No NJ Right-To-Know components exist in this product.

#### Pennsylvania Right-To-Know

The following non-hazardous ingredients are present in the product at greater than 3%.

No PA Right-To-Know components exist in this product.

#### California Proposition 65:

Warning: The following ingredients present in the product are known to the state of California to cause Cancer:

Chemical Name	CAS-No.		
ETHYL BENZENE	100-41-4		
CUMENE	98-82-8		
Warning: The following ingredients present in the product are known to the state of California to cause birth defects, or other reproductive hazards.			

No Proposition 65 Reproductive Toxins exist in this product.

## International Regulations: As follows -

### \* Canadian DSL:

No Information

#### 15.2 Chemical Safety Assessment:

No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.

# 16. Other Information

#### Text for GHS Hazard Statements shown in Section 3 describing each ingredient:

	5 5
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H373	May cause damage to organs through prolonged or repeated exposure.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

### Reasons for revision

No Information

No Information