Printing date 08/24/2016

Reviewed on 08/24/2016

1 Identification

- · Product identifier
- Trade name: <u>Anti Spall J33</u>
- · Article number: 83-69179
- Application of the substance / the mixture
- · Details of the supplier of the safety data sheet
- Manufacturer/Supplier: Dayton® Superior 4226 Kansas Avenue Kansas City, KS 66106

Tel.: (866) 329-8724

Emergency Telephone Number: Use only in the event of an emergency involving a spill, leak, fire, exposure, or accident involving chemicals. Within the U.S., Canada, or the U.S. Virgin Islands, call ChemTrec at (800) 424-9300, 24 hours a day. Or, outside these areas, call international number, +1 703 741-5970. Collect calls are accepted.

· Information department: Environmental, Health, and Safety department.

2 Hazard(s) identification

· Classification of the substance or mixture

Flam. Liq. 3 H226 Flammable liquid and vapor.	
Skin Irrit. 2 H315 Causes skin irritation.	
<i>Eye Irrit.</i> 2B H320 Causes eye irritation.	
Carc. 1B H350 May cause cancer.	
STOT RE 1 H372 Causes damage to the central nervous system through prolonged	or repeated exposure.
Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.	
Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.	

· Label elements

· GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).

· Hazard pictograms



· Signal word Danger

Hazard-determining components of labeling: Stoddard solvent
Naphtha (petroleum), hydrodesulfurized heavy
Distillates (petroleum), hydrotreated light
Solvent naphtha (petroleum), light arom.
Hazard statements
Flammable liquid and vapor.
Causes skin and eye irritation.
May cause cancer.
Causes damage to the central nervous system through prolonged or repeated exposure.
May be fatal if swallowed and enters airways.
Harmful to aquatic life with long lasting effects.
Precautionary statements
Wear protective gloves / eye protection / face protection.

Wear protective gloves / eye protection / face protection. IF SWALLOWED: Immediately call a POISON CENTER/ doctor.

Printing date 08/24/2016

Reviewed on 08/24/2016

Trade name: Anti Spall J33

(Contd. of page 1)
If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
Store locked up.
Dispose of contents/container in accordance with local/regional/national/international regulations.
Classification system: NFPA ratings (scale 0 - 4)
Health = 2
$\begin{array}{c} Fire = 2\\ Reactivity = 0 \end{array}$
HMIS-ratings (scale 0 - 4)
HEALTH ^{*2} Health = *2
FIRE 2 $Fire = 2$
PHYSICAL HAZARD O Reactivity = 0
Other hazards
Results of PBT and vPvB assessment
PBT: Not applicable. vPvB: Not applicable.
Composition/information on ingredients
Chemical characterization: Mixtures

• **Description:** Mixture of the substances listed below with nonhazardous additions.

· Dangerous d	components:	
64742-47-8	Distillates (petroleum), hydrotreated light	10-25%
8052-41-3	Stoddard solvent	10-25%
64742-82-1	Naphtha (petroleum), hydrodesulfurized heavy	10-25%
64742-95-6	Solvent naphtha (petroleum), light arom.	<u>≤</u> 2.5%
95-63-6	1,2,4-trimethylbenzene	<u>≤</u> 2.5%
103-65-1	propylbenzene	<i>≤</i> 1%
98-82-8	cumene	<i>≤</i> 1%

• Additional information: For the wording of the listed hazard phrases refer to section 16.

4 First-aid measures

3

- · Description of first aid measures
- After inhalation: Supply fresh air; consult doctor in case of complaints.

· After skin contact:

Immediately wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

- After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- · After swallowing: Seek medical treatment.

· Information for doctor:

• Most important symptoms and effects, both acute and delayed No further relevant information available.

· Indication of any immediate medical attention and special treatment needed No further relevant information available.

(Contd. on page 3)

US

Printing date 08/24/2016

Reviewed on 08/24/2016

Trade name: Anti Spall J33

(Contd. of page 2)

5 Fire-fighting measures

- · Extinguishing media
- Suitable extinguishing agents:
- CO2, sand, extinguishing powder. Do not use water. Foam
- · For safety reasons unsuitable extinguishing agents: Water
- Special hazards arising from the substance or mixture Formation of toxic gases is possible during heating or in case of fire.
- · Advice for firefighters
- · Protective equipment:

Because fire may produce thermal decomposition products, wear a self-contained breathing apparatus (SCBA) with a full face piece operated in pressure-demand or positive-pressure mode.

6 Accidental release measures

- Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.
- · Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

- Methods and material for containment and cleaning up:
- Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

· Handling:

· Precautions for safe handling

Wear appropriate personal protective clothing to prevent eye and skin contact. Avoid breathing vapors or mists of this product. Use with adequate ventilation. Do not take internally.

• Information about protection against explosions and fires: Keep ignition sources away - Do not smoke. Protect against electrostatic charges.

Keep respiratory protective device available.

- · Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep receptacle tightly sealed.
- Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

• Additional information about design of technical systems: No further data; see item 7.

(Contd. on page 4)

Printing date 08/24/2016

Reviewed on 08/24/2016

Trade name: Anti Spall J33

(Contd. of page 3) · Control parameters · Components with limit values that require monitoring at the workplace: The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits. 8052-41-3 Stoddard solvent PEL Long-term value: 2900 mg/m³, 500 ppm REL Long-term value: 350 mg/m³ Ceiling limit value: 1800* mg/m³ *15-min TLV Long-term value: 525 mg/m³, 100 ppm 95-63-6 1,2,4-trimethylbenzene REL Long-term value: 125 mg/m³, 25 ppm TLV Long-term value: 123 mg/m³, 25 ppm • Additional information: The lists that were valid during the creation were used as basis. · Exposure controls · Personal protective equipment: • General protective and hygienic measures: Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing. Wash hands before breaks and at the end of work. Store protective clothing separately. Avoid contact with the eyes and skin. · Breathing equipment: In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air. • Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed. • *Eye protection:* Wear appropriate eye protection to prevent eye contact.

9 Physical and chemical properties

- Information on basic physical and chemical properties
 General Information
- Appearance:Form:LiquidColor:According to product specification• Odor:Characteristic

(Contd. on page 5)

US

Printing date 08/24/2016

Reviewed on 08/24/2016

Trade name: Anti Spall J33

	(Contd. of page 4
· Odor threshold:	Not determined.
· pH-value:	Not determined.
• Change in condition Melting point/Melting range: Boiling point/Boiling range:	Undetermined. 121 °C (250 °F)
· Flash point:	39 °C (102 °F)
· Flammability (solid, gaseous):	Not applicable.
Ignition temperature:	210 °C (410 °F)
Decomposition temperature:	Not determined.
Auto igniting:	Product is not selfigniting.
Danger of explosion:	Product is not explosive. However, formation of explosive air/vapor mixtures are possible.
· Explosion limits: Lower: Upper:	0.5 Vol % 6.5 Vol %
· Vapor pressure at 20 °C (68 °F):	2 hPa (2 mm Hg)
· Density at 20 °C (68 °F): · Relative density · Vapor density · Evaporation rate	0.82292 g/cm ³ (6.867 lbs/gal) Not determined. Not determined. Not determined.
· Solubility in / Miscibility with Water:	Not miscible or difficult to mix.
· Partition coefficient (n-octanol/wate	e r): Not determined.
· Viscosity: Dynamic: Kinematic:	Not determined. Not determined.
· Solvent content: Organic solvents:	3.0 %
Solids content: • Other information	29.8 % No further relevant information available.
· Volatile Organic Compounds:	Contains less than 400 g/L.

10 Stability and reactivity

· Reactivity No decomposition if stored and applied as directed.

- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- \cdot **Possibility of hazardous reactions** No dangerous reactions known.
- \cdot Conditions to avoid Keep away from heat and sources of ignition.
- $\cdot \textit{Incompatible materials:} No further relevant information available.$
- · Hazardous decomposition products: No dangerous decomposition products known.

(Contd. on page 6)

US

Printing date 08/24/2016

Reviewed on 08/24/2016

Trade name: Anti Spall J33

(Contd. of page 5)

Acute toxi	city:		
LD/LC50	values that	t are relevant for classification:	
64742-95-	6 Solvent i	naphtha (petroleum), light arom.	
Oral	LD50	>6800 mg/kg (rat)	
Dermal	LD50	>3400 mg/kg (rab)	
Inhalative	LC50/4 h	>10.2 mg/l (rat)	
	on: No sen		
Additional The produ Carcinoge Carcinoge	toxicolog ct shows th nic. nic catego	<i>ical information:</i> <i>ne following dangers according to internally approved calculation methods for preparations:</i> <i>ries</i>	
Additional The produc Carcinoge Carcinoge IARC (Int	toxicolog ct shows th nic. nic catego ernational	<i>ical information:</i> <i>ne following dangers according to internally approved calculation methods for preparations:</i>	
Additional The produc Carcinoge Carcinoge IARC (Int	toxicolog ct shows th nic. nic catego ernational cumene	<i>ical information:</i> <i>ne following dangers according to internally approved calculation methods for preparations:</i> <i>ries</i>	
Additional The product Carcinoge Carcinoge IARC (Intel 98-82-8 1330-20-7	toxicolog ct shows th nic. nic catego ernational cumene	ical information: he following dangers according to internally approved calculation methods for preparations: ries Y Agency for Research on Cancer)	
Additional The production Carcinoge IARC (Intr 98-82-8 1330-20-7 91-20-3	toxicolog ct shows th nic. nic catego ernational cumene xylene	ical information: the following dangers according to internally approved calculation methods for preparations: ries Agency for Research on Cancer) ene	
Additional The production Carcinoge IARC (Intr 98-82-8 1330-20-7 91-20-3	toxicolog ct shows th nic. nic catego ernational cumene xylene naphthale ethylbenz	ical information: the following dangers according to internally approved calculation methods for preparations: ries Agency for Research on Cancer) ene	
Additional The product Carcinoge IARC (Intr 98-82-8 1330-20-7 91-20-3 100-41-4 7440-48-4	toxicolog ct shows th nic. nic catego ernational cumene xylene naphthala ethylbenz cobalt	ical information: the following dangers according to internally approved calculation methods for preparations: ries Agency for Research on Cancer) ene	
Additional The product Carcinoge IARC (Intr 98-82-8 1330-20-7 91-20-3 100-41-4 7440-48-4	toxicolog ct shows th nic. nic catego ernational cumene xylene naphthale ethylbenz cobalt	ical information: he following dangers according to internally approved calculation methods for preparations: ries Agency for Research on Cancer) ene gene	

12 Ecological information

· Toxicity

- Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- Bioaccumulative potential No further relevant information available.
- Mobility in soil No further relevant information available.
- · Ecotoxical effects:
- · Remark: Harmful to fish
- Additional ecological information:
- · General notes:
- Water hazard class 3 (Self-assessment): extremely hazardous for water

Do not allow product to reach ground water, water course or sewage system, even in small quantities.

Water hazard class 1 (Self-assessment): slightly hazardous for water

Harmful to aquatic organisms

- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.

(Contd. on page 7)

(Contd. of page 6)

Safety Data Sheet acc. to OSHA HCS

Printing date 08/24/2016

Reviewed on 08/24/2016

Trade name: Anti Spall J33

· Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of as normal garbage. Do not allow product to reach sewage system. It is the generator's responsibility to determine if the waste meets applicable definitions of hazardous waste. State and local regulations may differ from federal disposal regulations. Dispose of waste material according to local, state, federal, and provincial environmental regulations.

· Uncleaned packagings:

• Recommendation: Disposal must be made according to Federal, State, and Local regulations.

UN-Number		
DOT, ADR, IMDG, IATA	UN1268	
UN proper shipping name		
DOT, IATA	Petroleum distillates, n.o.s.	
ADR	1268 Petroleum distillates, n.o.s.	
IMDG	PETROLEUM DISTILLATES, N.O.S.	
Transport hazard class(es)		
DOT		
PLANARE E GURT		
Class	3 Flammable liquids	
Label	3	
ADR, IMDG, IATA		
Class	3 Flammable liquids	
Label	3	
Packing group		
DOT, ĂĎR, ÎMDG, IATA	III	
Environmental hazards:		
Marine pollutant:	No	
Special precautions for user	Warning: Flammable liquids	
Danger code (Kemler):	30	
EMS Number:	F-E,S-E	
Transport in bulk according to Annex II of A	MARPOL73/78	
and the IBC Code	Not applicable.	

US

Printing date 08/24/2016

Reviewed on 08/24/2016

Trade name: Anti Spall J33

	(Contd. of page 7
· Transport/Additional information:	
· ADR	
· Excepted quantities (EQ)	Code: E1
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 1000 ml
U.S. Domestic Ground Shipments:	Combustible liquids, n.o.s. (Petroleum Distillates), NA1993, PG
	111
· U.S. Domestic Ground Non-Bulk (119 gal or less per	
container) Shipments:	DOT: Not regulated (Reclassified as per 49CFR 173.150).
· Emergency Response Guide (ERG) Number:	Not determine
·IMDG	
Limited quantities (LQ)	5L
Excepted quantities (EQ)	Code: E1
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 1000 ml
· UN ''Model Regulation'':	UN 1268 PETROLEUM DISTILLATES, N.O.S., 3, III

15 Regulatory information

· Safety, health and environmental regulations/legislation specific for the substance or mix	cture
· Sara	

· Section 35.	o (extremely	hazardous	substances):
---------------	--------------	-----------	--------------

None of the ingredient is listed.

· Section 313 (Specific toxic chemical listings):

This product may contain 1 or more toxic chemicals subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act (SARA) of 1986 and 40 CFR part 372. If so, the chemicals are listed below.

× •		
95-63-6	1,2,4-trimethylbenzene	≤2.5%
98-82-8	cumene	<i>≤</i> 1%
1330-20-7		<i>≤</i> 0.1%
91-20-3	naphthalene	<i>≤</i> 0.1%
100-41-4	ethylbenzene	<i>≤</i> 0.1%
7440-48-4	cobalt	<i>≤</i> 0.1%
7439-96-5	manganese	<u>≤</u> 0.1%
· TSCA (Tox	cic Substances Control Act):	

All ingredients are listed.

· Proposition 65

64742-95-6 Solvent naphtha (petroleum), light arom.

98-82-8 cumene

91-20-3 naphthalene

100-41-4 ethylbenzene

7440-48-4 cobalt

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

(Contd. on page 9)

Printing date 08/24/2016

Reviewed on 08/24/2016

Trade name: Anti Spall J33

Chemicals	known to cause reproductive toxicity for males:	(Contd. of page
	e ingredients is listed.	
Chemicals	known to cause developmental toxicity:	
	e ingredients is listed.	
Canceroge	enity categories	
-	ironmental Protection Agency)	
98-82-8	cumene	D, CB
1330-20-7	xylene	Ι
91-20-3	naphthalene	C, CB
100-41-4	ethylbenzene	D
7439-96-5	manganese	D
TLV (Thre	eshold Limit Value established by ACGIH)	
1330-20-7	xylene	A
91-20-3	naphthalene	A
100-41-4	ethylbenzene	A
7440-48-4	cobalt	A
MAK (Ger	man Maximum Workplace Concentration)	·
91-20-3	naphthalene	2
100-41-4	ethylbenzene	3
7440-48-4	cobalt	2

None of the ingredients is listed.

• GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS). · Hazard pictograms



· Signal word Danger

· Hazard-determining components of labeling:

Stoddard solvent *Naphtha (petroleum), hydrodesulfurized heavy* Distillates (petroleum), hydrotreated light Solvent naphtha (petroleum), light arom.

· Hazard statements Flammable liquid and vapor. Causes skin and eye irritation. May cause cancer. Causes damage to the central nervous system through prolonged or repeated exposure. May be fatal if swallowed and enters airways. Harmful to aquatic life with long lasting effects. · Precautionary statements

Wear protective gloves / eye protection / face protection. IF SWALLOWED: Immediately call a POISON CENTER/ doctor. If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

(Contd. of page 9)

Safety Data Sheet acc. to OSHA HCS

Printing date 08/24/2016

Reviewed on 08/24/2016

Trade name: Anti Spall J33

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· National regulations:

· Information about limitation of use:

Workers are not allowed to be exposed to the hazardous carcinogenic materials contained in this preparation. Exceptions can be made by the authorities in certain cases.

- Water hazard class: Water hazard class 3 (Self-assessment): extremely hazardous for water.
- · Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

The provided information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship. This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: Environmental, Health & Safety Department
- · Contact: Environmental, Health & Safety Manager
- · Date of preparation / last revision 08/24/2016 / 65
- · Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods DOT: US Department of Transportation IATA: International Air Transport Association ACGIH: American Conference of Governmental Industrial Hygienists EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA) LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative NIOSH: National Institute for Occupational Safety

- OSHA: Occupational Safety & Health
- TLV: Threshold Limit Value
- PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

Flam. Liq. 3: Flammable liquids, Hazard Category 3

Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2

Eye Irrit. 2B: Serious eye damage/eye irritation, Hazard Category 2B

Carc. 1B: Carcinogenicity, Hazard Category 1B

STOT RE 1: Specific target organ toxicity - Repeated exposure, Hazard Category 1

Asp. Tox. 1: Aspiration hazard, Hazard Category 1

Aquatic Chronic 3: Hazardous to the aquatic environment - Chronic Hazard, Category 3