

# Safety Data Sheets (SDS)

For

## **CONCRETE PRODUCTS (Precast and Precast Prestressed Concrete)**

**Product Identifiers:** Precast/Prestressed Concrete, Architectural Precast Concrete, Structural Precast Concrete, Glass Fiber Reinforced Concrete, Bridge Products.

### **Section 1. Identification**

Material Identity (Trade Names): Precast/Prestressed Concrete Products

Manufacturer's Name:  
Northeast Prestressed Products, LLC.

Emergency Telephone Number:  
570-385-2352

Address:  
121 River Street, Cressona, PA 17929

Telephone Number for Information:  
570-385-2352

**Recommended Use:** Precast Concrete is widely used as a building or bridge component in many construction applications. This SDS covers many types of Concrete mixtures. Individual composition of hazardous constituents may vary between types / different mixture designs of Concrete.

**Recommended Restrictions:** None known

### **Section 2. Hazards Identification**

If the precast concrete member is to be modified in any way, e.g. by drilling, grinding, cutting, crushing, or abrasive blasting on site, the entity performing the modification is to comply with applicable OSHA respirable crystalline silica standards, i.e. CFR 1910.1053 and/or CFR 1926.1153. Use proper engineering controls, work practices, and personal protective equipment (PPE) to prevent exposure to respirable crystalline silica and concrete dust.

#### **GHS Label Elements**

The product is classified according to the Global Harmonized System (GHS)

#### **Hazard pictograms**



GHS08



GHS07

### Potential Health Effects

#### Acute Eye:

Eye contact to airborne concrete dust may cause immediate or delayed irritation or inflammation.

#### Acute Skin:

Skin contact with concrete dust may cause irritation

#### Acute Inhalation:

Cutting, grinding, crushing, drilling precast concrete products may generate dust containing respirable crystalline silica. Repeated exposures to very high levels of respirable crystalline silica (quartz) for periods as short as six months may cause acute silicosis.

Acute silicosis is a rapidly progressive, incurable lung disease that is typically fatal. Symptoms include (but are not limited to): shortness of breath, cough, fever, weight loss, and chest pain.

#### Chronic effects:

Prolonged over exposure to respirable dusts in excess of allowable exposure limits may cause inflammation of the lungs leading to possible fibrotic changes, a medical condition known as pneumoconiosis (lung disease). Prolonged and repeated inhalation of respirable crystalline silica containing dust in excess of allowable exposure limits may cause a form of silicosis, an incurable non-cancerous lung disease that may result in permanent lung damage or death. Chronic silicosis generally occurs after 10 years or more of over exposure; a more accelerated type of silicosis may occur between 5-10 years of higher levels of exposure. Silicosis can be progressive and symptoms can appear at any time, even years after exposure has ceased. Symptoms of silicosis may include, but are not limited to, the following: shortness of breath; difficulty breathing with or without exertion; coughing; diminished chest expansion; reduction of lung volume; right heart enlargement and/or failure. Persons with silicosis have an increased risk of pulmonary tuberculosis infection. Smoking aggravates the effects of silica exposure.

### Section 3. Composition / Information on Ingredients

This Safety Data Sheet covers various concrete mixture designs. The concrete contains mixtures of Portland or blended cements, other cementitious materials, such as slag, flyash, and other pozzolans, aggregates, chemical admixtures (chemical admixtures are present in quantities comprising less than 1% of the material) and water. Each of these ingredients may have quartz (silica) as a component. The percent of silica can vary greatly from product to product. Other ingredients such as fiber or pigment may be added and may include small amounts of organic and inorganic materials. Any concentration shown as a range is to protect confidentiality as a trade secret.

Material	SiO <sub>2</sub> Content, %
Portland Cement	22
Class F fly ash	52
Class C fly ash	35
Slag cement	35
Silica fume	85-97 (amorphous)
Igneous aggregates Granite Quartz Basalt	20-100 (typically 20-45)

Sedimentary aggregates Dolomite Limestone Sandstone	1-20
--	------

Hazardous Components (Chemical Identity/Common Names)	CAS No.	Percent (Weight/Weight of Materials)
Hydraulic Cement(s) Portland and/or Slag Cement	65997-15-1	3%-30%
Limestone (Calcium Carbonate $C_aCO_3$ ) Coarse Aggregate Fine Aggregate	1317-65-3	0-80% 30% to 60% 20% to 50%
Aggregate (sand, gravel, slag, expanded shale) Crystalline Silica (Quartz and Igneous) Coarse Aggregate Fine Aggregate	14808-60-7	20% to 80%  30% to 60% 20% to 50%
Fly Ash	68131-74-8	0%-5%
Silica Fume (Amorphous Silica)	7631-86-9	≤3
Iron Oxide Pigments	1309-37-1, 20344-49-4, 1317-61-9	≤3
Particulates not otherwise Classified	N/A	N/A

There are no additional ingredients present which, within the current knowledge of the supplier and in concentrations applicable, are classified as hazardous to the health or the environment and hence require reporting in this section.

#### Section 4. First Aid Measures

**For concrete dust:**

**Eye contact:** Rinse eyes thoroughly with water for at least 15 minutes, including under lids, to remove all particles. Seek medical attention for abrasions and burns or if irritation persists.

**Inhalation:** Dusts from hardened product may irritate the mouth, throat and lungs. Remove person to fresh air. Encourage individual to cough, spit out and blow nose to remove dust. Dust in throat and nasal passages should clear spontaneously. Contact a physician if irritation persists or later develops.

**Ingestion:** Do not induce vomiting. If conscious, have person drink plenty of water. Seek medical attention or contact poison control center immediately.

#### Section 5. Firefighting Measures

<b>Flash Point:</b> Not Combustible	<b>Flammable Limits:</b> Not Flammable	<b>LEL:</b> N/A	<b>UEL:</b> N/A
<b>Extinguishing Media:</b> This material is noncombustible. Use extinguishing media appropriate to surrounding fire			
<b>Unusual Fire and Explosion: Hazards:</b> None reported. Spalling of hardened concrete may occur under conditions of intense heat. Avoid breathing dust.			

### Section 6. Accidental Release Measures

Hardened concrete is not listed as a hazardous waste under designations by the EPA or DOT. Use dust control measures to minimize generation of airborne dust. Avoid inhalation of dust. Wetting the concrete prior to cleanup may be necessary to suppress dust. Wear appropriate personal protective equipment (PPE). Follow applicable Federal, State, and Local regulations governing waste disposal.

### Section 7. Handling and Storage

Respirable crystalline silica-containing dust may be generated during crushing, cutting, grinding, or drilling concrete products, handling and storage. Use all appropriate measures of dust control or suppression, and personal protective equipment (PPE) described in section 8. Use engineering controls (e.g. wetting stockpiles) to prevent windblown dust.

### Section 8. Exposure Controls/Personal Protection

#### Exposure Guidelines:

Component	OSHA- PELs (Permissible Exposure Limits)	OSHA -ALs (Action Levels)
Crystalline silica (Quartz) (Concrete contains aggregate materials which may contain crystalline silica)	50 µg/m <sup>3</sup>	25 µg/m <sup>3</sup>
Particulates not otherwise classified	15 mg/m <sup>3</sup> (Total) 5 mg/m <sup>3</sup> (Respirable)	

Use proper engineering controls, work practices, and Personal Protective Equipment (PPE) to prevent exposure to respirable silica dust.

**Engineering Controls:** When cutting, grinding, crushing or drilling hardened concrete, general or local ventilation systems may be necessary to maintain airborne dust concentrations below the OSHA PEL's. Local vacuum collection is preferred since it prevents release of contaminants into the work area by controlling it at the source. If a risk assessment indicates engineering controls or

work practice changes do not reduce the concentration of respirable silica dust below recommended limits, wear a properly fitted suitable NIOSH approved respirator. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the assigned protection factor of the selected respirator. The need for respiratory protection should be evaluated by a qualified safety professional, industrial hygienist, or other suitably knowledgeable individual prior to respirator selection and use. The use of respirators for controlling exposures in excess of the PEL must comply with OSHA requirements for medical surveillance, respiratory fit testing, repair and cleaning, and user training. In dusty areas, air monitoring for dust and quartz should be conducted regularly. Dust and quartz levels in excess of appropriate exposure limits should be reduced by all feasible engineering controls, including but not limited to, wet suppression, dilution, ventilation, process enclosure, and enclosed employee work stations.

**Eye/Face Protection:** When cutting, grinding, crushing or drilling hardened concrete, wear safety glasses with side shields, or goggles as minimum protection when engaged in activities where respirable silica dust could contact the eye. In extremely dusty environments and unpredictable environments wear unvented or indirectly vented goggles to avoid eye irritation or injury. Wearing contact lenses in dusty conditions is not recommended. (See OSHA 29 CFR 1926.103)

### Section 9. Physical and Chemical Properties

Physical State:	Solid	Lower and Upper explosive (flammable) limits:	No test data available
Color:	Various (gray or white, unless colored by admixture)	Vapor Pressure:	Not Applicable
Odor:	Odorless	Vapor Density:	Not Applicable
Odor Threshold:	Not Applicable	Relative Density:	1.5 - 3.0
ph (as a solid)	Not Applicable	Solubility:	Not Applicable
Melting Point:	Not Applicable	Solubility in Water:	Insoluble
Boiling Point:	Not Applicable	Partition Coefficient: n-octanol/water:	Not Applicable
Flash Point:	Not Applicable	Auto-ignition Temperature:	Not Applicable
Burning Time:	Not Applicable	Decomposition Temperature:	Not Applicable
Burning rate:	Not Applicable	Freezing Point:	Not Applicable
Evaporation Rate:	Not Applicable	Viscosity:	Not Applicable
Flammability (solid, gas)	No		

### Section 10. Stability and Reactivity

Reactivity:	Stable under normal conditions of use.
Chemical stability:	The product is stable.

Possibility of hazardous reactions:	Under normal conditions of storage and use, hazardous reactions will not occur
Conditions to avoid:	No specific data
Incompatible materials:	Hardened concrete will react with most acids in a neutralization-type reaction. Heat, spattering and evolution of (such as HCl, NO, or NO <sub>2</sub> ) may result depending on the acid involved. Prolonged contact of an acid with the concrete may cause etching or other damage. potentially toxic gases
Hazardous decomposition products:	Under normal conditions of storage and use, hazardous decomposition products should not be produced.
Hazardous polymerization:	Will not occur

### Section 11. Toxicology Information

The major concern is silicosis, caused by the inhalation and retention of respirable crystalline silica dust. Silicosis can exist in several forms: chronic or acute. Simple silicosis may develop into complicated silicosis or progressive massive fibrosis (PMF). Complicated silicosis or PMF is characterized by lung lesions (shown as radiographic opacities) greater than 1 centimeter in diameter. Advanced complicated silicosis or PMF may lead to death or heart disease secondary to the lung disease.

Concrete products are not listed as a carcinogen by OSHA. Limited evidence is available to suggest that respirable crystalline silica may pose a carcinogen threat to humans through prolonged or repeated exposure and level of exposure. This effect is more pronounced in those with silicosis.

### Section 12. Ecological

Toxicity:	Hardened concrete is inert
Persistence and degradability:	Not applicable
Bioaccumulation potential:	Not applicable
Mobility in soil:	Not applicable
Other adverse effects:	No known significant effects or critical hazards
Ecotoxicity:	No recognized unusual toxicity to plants or animals

**Section 13. Disposal Considerations**

Disposal methods: Can be recycled. Inert. Dispose of waste hardened material in a designated area or landfill in compliance with Local, State and Federal laws and regulations.

**Section 14. Transport Information**

This product is not classified as a Hazardous Material under U.S.DOT regulations.

**Section 15. Regulatory Information****OSHA Hazard Communication:**

This product, in an unmodified state, is not considered by OSHA to be hazardous and need not be included in the employer's hazard communication program. The hazards described in this SDS apply to the product if aerosol or respirable dusts are generated from use (cutting, grinding, drilling, abrasive blasting, pulverizing, etc.) Crystalline silica (airborne particulates of respirable size) generated during use is a substance known to be a carcinogen.

**Section 16. Other Information**

Approval date or revision date: To be added after TAC Review

Date of previous SDS: N/A

**Notice to reader:** The information contained in this Safety Data Sheet is based on hazard information from sources considered technically reliable and has been prepared in good faith in accordance with available information. The SDS should not be construed as the sum of all protective measures that may be taken. It is the responsibility of the employer to evaluate the information and to determine the extent of the hazard and what personal protective measures should be taken. Employers must ensure that SDS's are readily accessible to employees.

Nov. 2016