SAFETY DATA SHEET

1. Identification

Tariff code

Product identifier Liquid Wrench Penetrant & Lubricant

Other means of identification

SDS number LED411 LED411 Part No.

Penetrant/Lubricant Recommended use

Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

Manufacturer

Company name **RSC Chemical Solutions Address** 600 Radiator Road Indian Trail, NC 28079

United States

3403.19.1000

Customer Service: (704) 821-7643 Telephone

Technical: (704) 684-1811

Website www.rscbrands.com

E-mail sds@rscbrands.com

Emergency Telephone: Emergency phone number (303) 623-5716

Emergency Contact: RMPDC (877) 740-5015

2. Hazard(s) identification

Physical hazards Flammable aerosols Category 1 **Health hazards** Skin corrosion/irritation Category 2 Serious eye damage/eye irritation Category 2

Category 1B Sensitization, skin

Specific target organ toxicity, single exposure Category 3 narcotic effects Aspiration hazard Category 1

Hazardous to the aquatic environment, **Environmental hazards** Category 2

long-term hazard

OSHA defined hazards Not classified.

Label elements



Signal word Danger

Hazard statement Extremely flammable aerosol. May be fatal if swallowed and enters airways. Causes skin irritation.

May cause an allergic skin reaction. Causes serious eye irritation. May cause drowsiness or

dizziness. Toxic to aquatic life with long lasting effects.

Precautionary statement Prevention

Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Avoid breathing gas. Avoid breathing mist or vapor. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Contaminated work clothing must not be allowed out of the workplace. Avoid release to the environment. Wear eye protection/face protection. Wear protective gloves.

SDS US LED411 Version #: 02 Revision date: 06-06-2017 Issue date: 02-08-2017

If swallowed: Immediately call a poison center/doctor. Do NOT induce vomiting. If on skin: Wash Response

with plenty of water. If inhaled: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a poison center/doctor if you feel unwell. If skin irritation or rash occurs: Get medical advice/attention. If eye irritation persists: Get medical advice/attention. Take

off contaminated clothing and wash before reuse. Collect spillage.

Storage Store in a well-ventilated place. Keep container tightly closed. Store locked up. Protect from

sunlight. Do not expose to temperatures exceeding 50°C/122°F.

Dispose of contents/container in accordance with local/regional/national/international regulations. Disposal

Hazard(s) not otherwise classified (HNOC)

Combustible.

Supplemental information 77.78% of the mixture consists of component(s) of unknown acute oral toxicity. 77.78% of the

mixture consists of component(s) of unknown acute dermal toxicity. 89.91% of the mixture consists of component(s) of unknown acute inhalation toxicity. 35.66% of the mixture consists of component(s) of unknown long-term hazards to the aquatic environment.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
Distillates (petroleum), Hydrotreated Light		64742-47-8	40 - < 50
2-(2-butoxyéthoxy) Éthanol		112-34-5	10 - < 20
Distillates (petroleum), Hydrotreated Heavy Naphthenic		64742-52-5	10 - < 20
1,6,10-dodecatriene, 7,11-dimethyl-3-methylene-, (6e)-, Hydrogenated		1581740-29-5	5 - < 10
Soybean Oil		8001-22-7	5 - < 10
Corrosion Inhibitor		Mixture	3 - < 5
Carbon Dioxide		124-38-9	1 - < 3
Bht (butylated Hydroxytoluene)		128-37-0	< 0.2
Other components below reportable le	evels		3 - < 5

^{*}Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

Inhalation Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON

CENTER or doctor/physician if you feel unwell.

Remove contaminated clothing immediately and wash skin with soap and water. In case of Skin contact

eczema or other skin disorders: Seek medical attention and take along these instructions. Wash

contaminated clothing before reuse.

Eye contact Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if

present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.

Call a physician or poison control center immediately. Rinse mouth. Do not induce vomiting. If Ingestion

vomiting occurs, keep head low so that stomach content doesn't get into the lungs.

Most important

General information

symptoms/effects, acute and

delayed

Aspiration may cause pulmonary edema and pneumonitis. May cause drowsiness and dizziness. Headache. Nausea, vomiting. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May cause redness and pain. May cause an

allergic skin reaction. Dermatitis. Rash.

Indication of immediate medical attention and special

treatment needed

Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Wash contaminated clothing before reuse.

5. Fire-fighting measures

Suitable extinguishing media

Unsuitable extinguishing media

Alcohol resistant foam. Powder. Dry chemicals. Carbon dioxide (CO2). Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical

Contents under pressure. Pressurized container may explode when exposed to heat or flame. During fire, gases hazardous to health may be formed.

Material name: Liquid Wrench Penetrant & Lubricant LED411 Version #: 02 Revision date: 06-06-2017 Issue date: 02-08-2017 Special protective equipment and precautions for firefighters

Fire fighting equipment/instructions

Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

Move containers from fire area if you can do so without risk. Cool containers exposed to heat with water spray and remove container, if no risk is involved. Containers should be cooled with water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.

Specific methods

Use standard firefighting procedures and consider the hazards of other involved materials. Move containers from fire area if you can do so without risk. In the event of fire and/or explosion do not breathe fumes.

General fire hazards

Extremely flammable aerosol. Combustible.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Avoid breathing mist or vapor. Avoid breathing gas. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up

Refer to attached safety data sheets and/or instructions for use. Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Use water spray to reduce vapors or divert vapor cloud drift. Isolate area until gas has dispersed. Keep combustibles (wood, paper, oil, etc.) away from spilled material. Prevent product from entering drains. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. For waste disposal, see section 13 of the SDS.

Environmental precautions

Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling

Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. All equipment used when handling the product must be grounded. Do not re-use empty containers. Avoid breathing mist or vapor. Avoid breathing gas. Avoid contact with eyes, skin, and clothing. Avoid prolonged or repeated contact with skin. Avoid prolonged exposure. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Avoid release to the environment. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Level 2 Aerosol.

Store locked up. Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122°F. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Keep out of the reach of children. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Type	Value	Form
Carbon Dioxide (CAS 124-38-9)	PEL	9000 mg/m3	
•		5000 ppm	
Distillates (petroleum), Hydrotreated Heavy Naphthenic (CAS 64742-52-5)	PEL	5 mg/m3	Mist.
· · · · · · · · · · · · · · · · · · ·		2000 mg/m3	
		500 ppm	

Material name: Liquid Wrench Penetrant & Lubricant

Components	for Air Contaminants (29 CFR 1910.1000) Type	Value	Form
Distillates (petroleum), Hydrotreated Light (CAS 64742-47-8)	PEL	400 mg/m3	
· · · · · · · · · · · · · · · · · · ·		100 ppm	
Soybean Oil (CAS 8001-22-7)	PEL	5 mg/m3	Respirable fraction.
,		15 mg/m3	Total dust.
US. ACGIH Threshold Limit Components	Values Type	Value	Form
2-(2-butoxyéthoxy) Éthanol	TWA	10 ppm	Inhalable fraction and
(CAS 112-34-5)	T14/4	0 / 0	vapor.
Bht (butylated Hydroxytoluene) (CAS 128-37-0)	TWA	2 mg/m3	Inhalable fraction and vapor.
Carbon Dioxide (CAS 124-38-9)	STEL	30000 ppm	
00 0,	TWA	5000 ppm	
Distillates (petroleum), Hydrotreated Heavy Naphthenic (CAS 64742-52-5)	TWA	5 mg/m3	Inhalable fraction.
US. NIOSH: Pocket Guide to	Chemical Hazards		
Components	Туре	Value	Form
Bht (butylated Hydroxytoluene) (CAS 128-37-0)	TWA	10 mg/m3	
Carbon Dioxide (CAS 124-38-9)	STEL	54000 mg/m3	
		30000 ppm	
	TWA	9000 mg/m3	
Distillates (petroleum),	Ceiling	5000 ppm 1800 mg/m3	
Hydrotreated Heavy Naphthenic (CAS 64742-52-5)	Colling	1000 mg/ms	
	STEL	10 mg/m3	Mist.
Soybean Oil (CAS 8001-22-7)	TWA	5 mg/m3	Respirable.
		10 mg/m3	Mist.
logical limit values	No biological exposure limits noted for the	e ingredient(s).	
propriate engineering trols	Good general ventilation (typically 10 air of should be matched to conditions. If applic or other engineering controls to maintain exposure limits have not been established eyewash station. Eye wash fountain and of the statement of the statemen	cable, use process enclosur airborne levels below recor d, maintain airborne levels	es, local exhaust ventilation, nmended exposure limits. If to an acceptable level. Provid
vidual protection measures,	such as personal protective equipment		
Eye/face protection	Wear safety glasses with side shields (or	goggles) or a face shield.	
Skin protection Hand protection	Wear appropriate chemical resistant glove	es.	
Other	Wear appropriate chemical resistant cloth	ning.	
Respiratory protection	Chemical respirator with organic vapor ca organic vapor cartridge and full facepiece		
Thermal hazards	Wear appropriate thermal protective cloth		
neral hygiene siderations	When using do not smoke. Always observafter handling the material and before eat clothing and protective equipment to remove allowed out of the workplace.	ting, drinking, and/or smoki	ng. Routinely wash work

SDS US

9. Physical and chemical properties

Appearance Opaque Liquid
Physical state Liquid, Gas.
Form Aerosol.

ColorLight brownto Tan.OdorSweet VanillaOdor thresholdNot available.pHNot available.

Melting point/freezing point -90.58 °F (-68.1 °C) estimated Initial boiling point and boiling 446.72 °F (230.4 °C) estimated

range

Flash point > 200.0 °F (> 93.3 °C) Tag Closed Cup

Evaporation rate Not available.

Flammability (solid, gas) Not applicable. Not available.

Upper/lower flammability or explosive limits

Flammability limit - lower

0.7 % estimated

(%)

Flammability limit - upper

5 % estimated

(%)

Explosive limit - lower (%) Not available.

Explosive limit - upper (%) Not available.

Vapor pressure 0.43 hPa estimated

Vapor densityNot available.Relative densityNot available.

Solubility(ies)

Solubility (water) Not available.

Partition coefficient Not available.

(n-octanol/water)

Auto-ignition temperature 442 °F (227.78 °C) estimated

Decomposition temperature Not available. **Viscosity** Not available.

Other information

Density 6.93 lbs/gal
Explosive properties Not explosive.
Flame extension > 31 in

Flammability (flash back) No

Heat of combustion (NFPA

30B)

27.16 kJ/g estimated

Oxidizing properties Not oxidizing.

Percent volatile 14.63 % estimated

Specific gravity 0.83

VOC > 1 % w/w

10. Stability and reactivity

ReactivityThe product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions.

Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

Conditions to avoid Avoid temperatures exceeding the flash point. Contact with incompatible materials.

Incompatible materials Strong oxidizing agents.

Hazardous decomposition No hazardous decomposition products are known.

products

Material name: Liquid Wrench Penetrant & Lubricant
LED411 Version #: 02 Revision date: 06-06-2017 Issue date: 02-08-2017

11. Toxicological information

Information on likely routes of exposure

May cause drowsiness and dizziness. Headache. Nausea, vomiting. Prolonged inhalation may be Inhalation

harmful.

Skin contact Causes skin irritation. May cause an allergic skin reaction.

Eve contact Causes serious eye irritation.

Ingestion Droplets of the product aspirated into the lungs through ingestion or vomiting may cause a serious

chemical pneumonia.

Symptoms related to the physical, chemical and toxicological characteristics Aspiration may cause pulmonary edema and pneumonitis. May cause drowsiness and dizziness. Headache, Nausea, vomiting, Severe eve irritation, Symptoms may include stinging, tearing. redness, swelling, and blurred vision. Skin irritation. May cause redness and pain. May cause an

allergic skin reaction. Dermatitis. Rash.

Information on toxicological effects

Acute toxicity May be fatal if swallowed and enters airways.

Components **Test Results Species**

2-(2-butoxyéthoxy) Éthanol (CAS 112-34-5)

Acute

Dermal

LD50 Rabbit 2700 mg/kg

Oral

LD50 Rat 4500 mg/kg

Bht (butylated Hydroxytoluene) (CAS 128-37-0)

Acute

Oral

LD50 Rat 890 mg/kg

Skin corrosion/irritation Causes skin irritation.

Serious eye damage/eye

Causes serious eye irritation.

irritation

Respiratory or skin sensitization

Respiratory sensitization Not a respiratory sensitizer.

Skin sensitization May cause an allergic skin reaction.

Germ cell mutagenicity No data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Not classifiable as to carcinogenicity to humans. Carcinogenicity

IARC Monographs. Overall Evaluation of Carcinogenicity

Bht (butylated Hydroxytoluene) (CAS 128-37-0) 3 Not classifiable as to carcinogenicity to humans.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not regulated.

US. National Toxicology Program (NTP) Report on Carcinogens

Not listed.

This product is not expected to cause reproductive or developmental effects. Reproductive toxicity

Specific target organ toxicity -

single exposure

May cause drowsiness and dizziness.

Specific target organ toxicity -

repeated exposure

Not classified.

Aspiration hazard May be fatal if swallowed and enters airways.

Chronic effects Prolonged inhalation may be harmful.

12. Ecological information

Ecotoxicity Toxic to aquatic life with long lasting effects.

Material name: Liquid Wrench Penetrant & Lubricant SDS US LED411 Version #: 02 Revision date: 06-06-2017 Issue date: 02-08-2017

^{*} Estimates for product may be based on additional component data not shown.

Components Species Test Results

2-(2-butoxyéthoxy) Éthanol (CAS 112-34-5)

Aquatic

Fish LC50 Bluegill (Lepomis macrochirus) 1300 mg/l, 96 hours

Bht (butylated Hydroxytoluene) (CAS 128-37-0)

Aquatic

Crustacea EC50 Water flea (Daphnia pulex) 1.44 mg/l, 48 hours

Distillates (petroleum), Hydrotreated Light (CAS 64742-47-8)

Aquatic

Crustacea EC50 Water flea (Daphnia pulex) 2.7 - 5.1 mg/l, 48 hours

Fish LC50 Rainbow trout, donaldson trout 2.9 mg/l, 96 hours

(Oncorhynchus mykiss)

Persistence and degradability

Bioaccumulative potential

Partition coefficient n-octanol / water (log Kow)

1,6,10-dodecatriene, 7,11-dimethyl-3-methylene-, (6e)-, 6.08 - 6.48 OECD 117, Log Kow

Hydrogenated

2-(2-butoxyéthoxy) Éthanol 0.56

Mobility in soil No data available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructionsCollect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents

under pressure. Do not puncture, incinerate or crush. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international

regulations.

Local disposal regulations

Dispose in accordance with all applicable regulations.

Hazardous waste code

The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Contaminated packaging Since emptied containers may retain product residue, follow label warnings even after container is

emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal. Do not re-use empty containers.

14. Transport information

DOT

UN number Not available.

UN proper shipping name

Consumer Commodity

Transport hazard class(es)

Class ORM-D

Subsidiary risk -

Packing group Not available.

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Packaging exceptions 306
Packaging non bulk 302, 304
Packaging bulk 302, 314, 315

IATA

UN number UN1950

UN proper shipping name Aerosol, flammable

Transport hazard class(es)

Class 2.1 Subsidiary risk -

Packing group Not available.

^{*} Estimates for product may be based on additional component data not shown.

Environmental hazards Yes

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

IMDG

UN number UN1950

UN proper shipping name Aerosols, MARINE POLLUTANT

Transport hazard class(es)

Class 2.1 Subsidiary risk -

Packing group Not available.

Environmental hazards

Marine pollutant Yes EmS F-D, S-U

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Transport in bulk according to Not established.

Annex II of MARPOL 73/78 and the IBC Code

IATA; IMDG



Marine pollutant



General information IMDG Regulated Marine Pollutant.

15. Regulatory information

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication

Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

2-(2-butoxyéthoxy) Éthanol (CAS 112-34-5) Listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not regulated.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories Immediate Hazard - Yes

Delayed Hazard - No Fire Hazard - Yes Pressure Hazard - No Reactivity Hazard - No

SARA 302 Extremely hazardous substance

Not listed.

LED411 Version #: 02 Revision date: 06-06-2017 Issue date: 02-08-2017

SARA 311/312 Hazardous

chemical

SARA 313 (TRI reporting)

Chemical name	CAS number	% by wt.
2-(2-butoxyéthoxy) Éthanol	112-34-5	10 - < 20

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

No

2-(2-butoxyéthoxy) Éthanol (CAS 112-34-5)

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

Not regulated.

(SDWA)

US state regulations

California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins.

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

2-(2-butoxyéthoxy) Éthanol (CAS 112-34-5)

Distillates (petroleum), Hydrotreated Heavy Naphthenic (CAS 64742-52-5)

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	No
Canada	Domestic Substances List (DSL)	No
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	No
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	No
New Zealand	New Zealand Inventory	No
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	No

^{*}A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)
A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

Toxic Substances Control Act (TSCA) Inventory

16. Other information, including date of preparation or last revision

Issue date 02-08-2017 **Revision date** 06-06-2017

Version # 02

United States & Puerto Rico

HMIS® ratings Health: 3

Flammability: 1

Physical hazard: 0

NFPA ratings Health: 2

Flammability: 1 Instability: 0

NFPA ratings



Disclaimer The information provided in this Safety Data Sheet is correct to the best of our knowledge,

information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other

materials or in any process, unless specified in the text.

Yes

Revision information

Product and Company Identification: Product and Company Identification

Composition / Information on Ingredients: Ingredients

Fire-fighting measures: Special protective equipment and precautions for firefighters

Exposure controls/personal protection: Eye/face protection Exposure controls/personal protection: Eye/lace protect Exposure controls/personal protection: PPE Symbols Physical & Chemical Properties: Multiple Properties Physical and chemical properties: Color Ecological information: Other adverse effects Regulatory Information: TSCA 12b Exported Products

HazReg Data: International Inventories

GHS: Classification

Material name: Liquid Wrench Penetrant & Lubricant

10 / 10 LED411 Version #: 02 Revision date: 06-06-2017 Issue date: 02-08-2017