

Safety Data Sheet

Printing date 08/15/2017

Revised On 08/15/2017

1 Identification of the substance and manufacturer

Trade name: SAFETY ORANGE (MRO) GALLONS
Product code: 0000011451
Manufacturer/Supplier: Seymour of Sycamore
 917 Crosby Avenue
 Sycamore, IL 60178
 phone: 815-895-9101
 www.seymourpaint.com
Emergency telephone number: 1-800-255-3924

2 Hazard(s) identification**Classification of the substance or mixture**

Flam. Liq. 2 H225 Highly flammable liquid and vapor.

Eye Irrit. 2A H319 Causes serious eye irritation.

STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.

GHS Hazard pictograms

GHS02 GHS07 GHS08

Signal word

Danger

Hazard statements

Highly flammable liquid and vapor.

Causes serious eye irritation.

May cause damage to organs through prolonged or repeated exposure.

Precautionary statements

Keep away from heat/sparks/open flames/hot surfaces. No smoking.

Keep container tightly closed.

Ground/bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting/equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Do not breathe dust/fume/gas/mist/vapors/spray.

Wash hands thoroughly after handling.

Wear protective gloves/protective clothing/eye protection/face protection.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Get medical advice/attention if you feel unwell.

If eye irritation persists: Get medical advice/attention.

In case of fire: Use for extinction: CO2, powder or water spray.

Store in a well-ventilated place. Keep cool.

Dispose of contents/container in accordance with local/regional/national/international regulations.

3 Composition/information on ingredients**Chemical characterization: Mixtures****Chemical Description:**

This product is a mixture of the substances listed below with nonhazardous additions.

Dangerous components:

64742-47-8	Mineral Spirits	18.46%
7727-43-7	barium sulfate	14.96%
108-65-6	PM acetate	7.64%
13463-67-7	titanium dioxide	2.52%
64742-48-9	Naphtha, hydrotreated heavy	1.11%
1330-20-7	xylene (mix)	1.06%

4 First-aid measures

After skin contact: Remove contaminated clothing. Wash exposed area with soap and water.
After eye contact: Rinse opened eye for several minutes under running water.
After swallowing: Rinse mouth with water. Do not induce vomiting.
Most important symptoms and effects: No further relevant information available.
Indication of any immediate medical attention needed: No further relevant information available.

5 Fire-fighting measures

Special hazards: No further relevant information available.
Protective equipment for firefighters: No special measures required.

6 Accidental release measures

Personal precautions, protective equipment and emergency procedures: Not required.
Methods and material for containment and cleaning up: Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

(Contd. on page 2)

Safety Data Sheet

Printing date 08/15/2017

Revised On 08/15/2017

Trade name: SAFETY ORANGE (MRO) GALLONS

(Contd. of page 1)

7 Handling and storage**Precautions for safe handling**
Storage requirements:Use only in well ventilated areas.
Keep away from sources of heat and direct sunlight. Do not warehouse in subfreezing conditions. Store locked up.**8 Exposure controls/personal protection****Components with limit values that require monitoring at the workplace:****7727-43-7 barium sulfate**

PEL (USA)	Long-term value: 15* 5** mg/m ³ *total dust **respirable fraction
REL (USA)	Long-term value: 10* 5** mg/m ³ *total dust **respirable fraction
TLV (USA)	Long-term value: 5* mg/m ³ *inhalable fraction; E

108-65-6 PM acetate

WEEL (USA) Long-term value: 50 ppm

1330-20-7 xylene (mix)

PEL (USA)	Long-term value: 435 mg/m ³ , 100 ppm
REL (USA)	Short-term value: 655 mg/m ³ , 150 ppm Long-term value: 435 mg/m ³ , 100 ppm
TLV (USA)	Short-term value: 651 mg/m ³ , 150 ppm Long-term value: 434 mg/m ³ , 100 ppm BEI

Ingredients with biological limit values:**1330-20-7 xylene (mix)**

BEI (USA)	1.5 g/g creatinine Medium: urine Time: end of shift Parameter: Methylhippuric acids
-----------	--

Hygienic protection:Wash hands after use.
Do not eat or drink while working.**Breathing equipment:**

Not required.

Hand protection:Nitrile gloves.
The glove material must be impermeable and resistant to the substance.**Eye protection:**

Tightly sealed goggles

9 Physical and chemical properties

Appearance:	Liquid.
Odor threshold:	Not determined.
pH-value:	Not determined.
Melting point/Melting range	Undetermined.
Boiling point:	146 °C (295 °F)
Flash point:	-19 °C (-2 °F)
Flammability (solid, gas):	Highly flammable.
Decomposition temperature:	Not determined.
Auto igniting:	Product is not self-igniting.
Danger of explosion:	In use, may form flammable/explosive vapour-air mixture.
Lower Explosion Limit:	0.5 Vol %
Upper Explosion Limit:	6.5 Vol %
Vapor pressure:	Not determined.
Vapor density	Not determined.
Evaporation rate	Not determined.
Partition coefficient: n-octonal/water:	Not determined.
Solubility:	Not determined.
Viscosity:	Not determined.
VOC content:	324.9 g/l / 2.71 lb/gl
Solids content:	69.9 %

10 Stability and reactivity

Conditions to avoid:	No decomposition if used according to specifications.
Possibility of hazardous reactions:	No dangerous reactions known.
Incompatible materials:	No further relevant information available.
Hazardous decomposition:	No dangerous decomposition products known.

11 Toxicological information**LD/LC50 values that are relevant for classification:****108-65-6 PM acetate**

Oral	LD50	8500 mg/kg (rat)
------	------	------------------

(Contd. on page 3)

Safety Data Sheet

Printing date 08/15/2017

Revised On 08/15/2017

Trade name: SAFETY ORANGE (MRO) GALLONS

(Contd. of page 2)

Inhalative	LC50/4 h	35.7 mg/l (rat)
13463-67-7 titanium dioxide		
Oral	LD50	>20000 mg/kg (rat)
Dermal	LD50	>10000 mg/kg (rbt)
Inhalative	LC50/4 h	>6.82 mg/l (rat)
64742-48-9 Naphtha, hydrotreated heavy		
Oral	LD50	>5000 mg/kg (rat)
Dermal	LD50	>3000 mg/kg (rab)
1330-20-7 xylene (mix)		
Oral	LD50	8700 mg/kg (rat)
Dermal	LD50	2000 mg/kg (rbt)
Inhalative	LC50/4 h	6350 mg/l (rat)

Information on toxicological effects: No data available.
Skin effects: No irritant effect.
Eye effects: No irritating effect.
Sensitization: No sensitizing effects known.

12 Ecological information

Aquatic toxicity: Hazardous for water, do not empty into drains.
Persistence and degradability: The product is degradable after prolonged exposure to natural weathering processes.
Bioaccumulative potential: No further relevant information available.
Mobility in soil: No further relevant information available.
Other adverse effects: No further relevant information available.

13 Disposal considerations

Dispose of in accordance with local, state, and federal regulations. Do not puncture, incinerate, or compact. Partially empty cans must be disposed of responsibly. Do not heat or cut empty containers with electric or gas torches.
Recommendation: Completely empty cans should be recycled.

14 Transport information

UN-Number UN1263
ADR 1263 Paint
Transport hazard class(es):
Class 3 Flammable liquids
Marine pollutant: No
Special precautions for user: Warning: Flammable liquids
EMS Number: F-E,S-E
Quantity limitations On passenger aircraft/rail: 5 L
 On cargo aircraft only: 60 L

ADR
Excepted quantities (EQ) Code: E2
 Maximum net quantity per inner packaging: 30 ml
 Maximum net quantity per outer packaging: 500 ml

IMDG
Limited quantities (LQ) 5L
Excepted quantities (EQ) Code: E2
 Maximum net quantity per inner packaging: 30 ml
 Maximum net quantity per outer packaging: 500 ml

UN "Model Regulation": UN1263, Paint, 3, II

15 Regulatory information**SARA Section 355 (extremely hazardous substances):**

None of the ingredients in this product are listed.

SARA Section 313 (Specific toxic chemical listings):

7727-43-7 barium sulfate
 1330-20-7 xylene (mix)

Toxic Substances Control Act (TSCA):

All hazardous ingredients for this product are found on the inventory list of substances.

Consumer Product Safety**Comission (CPSC):**

This product complies with 16 CFR 1303 and does not contain more than 90 ppm of lead.

California Proposition 65 chemicals known to cause cancer:

13463-67-7 titanium dioxide
 100-41-4 ethyl benzene

California Proposition 65 chemicals known to cause birth defects or reproductive harm:

None of the ingredients in this product are listed.

CANADIAN ENVIRONMENTAL PROTECTION ACT:**WHMIS Symbols for Canada:**

All hazardous ingredients for this product appear on the Canadian Domestic Substance List.
 B2 - Flammable liquid

(Contd. on page 4)

Safety Data Sheet

Printing date 08/15/2017

Revised On 08/15/2017

Trade name: SAFETY ORANGE (MRO) GALLONS

(Contd. of page 3)

**EPA:**

7727-43-7	barium sulfate	D, CBD(inh), NL(oral)
1330-20-7	xylene (mix)	I

16 Other information

Contact: Regulatory Affairs
Date of preparation / last revision 08/15/2017 / -