Valvoline	Page: 1
SAFETY DATA SHEET	Revision Date: 01/15/2018
	Print Date: 1/16/2018
	SDS Number: R0296766
Zerex™ G-05 AntIfreeze	Version: 1.5
377726	

29 CFR 1910.1200 (OSHA HazCom 2012)

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product identifier

Trade name : Zerex™ G-05 AntIfreeze

Details of the supplier of the safety data sheet

Valvoline LLC 100 Valvoline Way Lexington, KY 40509 United States of America (USA) 1-800-TEAMVAL (1-800-832-6825) Emergency telephone number

1-800-VALVOLINE (1-800-825-8654)

Regulatory Information Number 1-800-TEAMVAL (1-800-832-6825)

Product Information

1-800-TEAMVAL (1-800-832-6825)

SECTION 2. HAZARDS IDENTIFICATION

GHS Classification

Acute toxicity (Oral) : Category 4

Reproductive toxicity : Category 1B

Specific target organ

systemic toxicity - repeated

exposure (Oral)

: Category 2 (Kidney, Liver)

GHS label elements

Hazard pictograms





Signal Word : Danger

Hazard Statements : Harmful if swallowed.

May damage fertility or the unborn child.

May cause damage to organs (Kidney, Liver) through

prolonged or repeated exposure if swallowed.

Precautionary Statements : Prevention:

Obtain special instructions before use.

Do not handle until all safety precautions have been read and

understood.

Valvoline.	Page: 2
SAFETY DATA SHEET	Revision Date: 01/15/2018
	Print Date: 1/16/2018
	SDS Number: R0296766
Zerex™ G-05 AntIfreeze	Version: 1.5
377726	

Do not breathe dust/ fume/ gas/ mist/ vapors/ spray.

Wash skin thoroughly after handling.

Do not eat, drink or smoke when using this product.

Wear protective gloves/ protective clothing/ eye protection/ face

protection. **Response:**

IF SWALLOWED: Call a POISON CENTER/doctor if you feel

unwell. Rinse mouth.

IF exposed or concerned: Get medical advice/ attention.

Storage:

Store locked up.

Disposal:

Dispose of contents/ container to an approved waste disposal

plant.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Hazardous components

CAS-No.	Classification	Concentration (%)
107-21-1	Acute Tox. 4; H302	94.0788
	STOT RE 2; H373	
111-46-6	Acute Toy 4: H302	4.7033
111-40-0	Acute 10x. 4, 11302	4.7033
	STOT RE 2; H373	
532-32-1	Eye Irrit. 2A; H319	2.5984
1330-43-4	Repr. 1B; H360	1.529
	107-21-1 111-46-6 532-32-1	107-21-1 Acute Tox. 4; H302 STOT RE 2; H373 111-46-6 Acute Tox. 4; H302 STOT RE 2; H373 532-32-1 Eye Irrit. 2A; H319

SECTION 4. FIRST AID MEASURES

General advice : Move out of dangerous area.

Show this safety data sheet to the doctor in attendance.

Do not leave the victim unattended.

If inhaled : If unconscious, place in recovery position and seek medical

Valvoline.	Page: 3
SAFETY DATA SHEET	Revision Date: 01/15/2018
	Print Date: 1/16/2018
	SDS Number: R0296766
Zerex™ G-05 AntIfreeze	Version: 1.5
377726	

advice.

If symptoms persist, call a physician.

In case of skin contact : First aid is not normally required. However, it is

recommended that exposed areas be cleaned by washing

with soap and water.

In case of eye contact : Flush eyes with water as a precaution.

Remove contact lenses. Protect unharmed eye.

If eye irritation persists, consult a specialist.

If swallowed : Obtain medical attention.

Rinse mouth with water.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

If symptoms persist, call a physician.

Most important symptoms and effects, both acute and delayed

: Effects of acute ethylene glycol poisoning appear in three fairly distinct stages. The initial stage occurs shortly after exposure, lasts 6-12 hours, and is characterized by central nervous system effects (transient exhilaration, nausea, vomiting, and in severe cases, coma, convulsions, and possible death). The second stage lasts from 12-36 hours after exposure and is initiated by the onset of coma. This phase is characterized by tachypnia, tachycardia, mild hypotension, cyanosis, and in severe cases, pulmonary edema, bronchopneumonia, cardiac enlargement, and congestive failure. The final stage occurs 24-72 postexposure and is characterized by renal failure, ranging from a mild increase in blood urea nitrogen and creatinine followed by recovery, to complete anuria with acute tubular necrosis that can lead to death. Oxaluria is found in most cases. The most significant laboratory finding in ethylene glycol intoxication is severe metabolic acidosis.

Signs and symptoms of exposure to this material through breathing, swallowing, and/or passage of the material through the skin may include:

stomach or intestinal upset (nausea, vomiting, diarrhea) irritation (nose, throat, airways)

Pariale

Cough

pain in the abdomen and lower back

cyanosis (causes blue coloring of the skin and nails from lack

of oxygen)

lung edema (fluid buildup in the lung tissue)

acute kidney failure (sudden slowing or stopping of urine

production) Convulsions

Harmful if swallowed.

Valvoline	Page: 4
SAFETY DATA SHEET	Revision Date: 01/15/2018
	Print Date: 1/16/2018
	SDS Number: R0296766
Zerex™ G-05 AntIfreeze	Version: 1.5
377726	

May damage fertility or the unborn child.

Notes to physician

This product contains ethylene glycol. Ethanol decreases the metabolism of ethylene glycol to toxic metabolites. Ethanol should be administered as soon as possible in cases of severe poisoning since the elimination half-life of ethylene glycol is 3 hours. If medical care will be delayed several hours, give the patient three to four 1-ounce oral "shots" of 86-proof or higher whiskey before or during transport to the hospital. Fomepizole (4-methylpyrazole) is an effective antagonist of alcohol dehydrogenase, and as such, may be used as an antidote in the treatment of ethylene glycol poisoning. Hemodialysis effectively removes ethylene glycol and its metabolites from the body.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media

: Use extinguishing measures that are appropriate to local

circumstances and the surrounding environment.

Water spray Foam

Carbon dioxide (CO2)

Dry chemical

Unsuitable extinguishing

media

: High volume water jet

Specific hazards during

firefighting

: Do not allow run-off from fire fighting to enter drains or water

courses.

Hazardous combustion

products

: Alcohols Aldehydes

carbon dioxide and carbon monoxide

ethers toxic fumes Hydrocarbons Sodium oxides

Specific extinguishing

methods

: Product is compatible with standard fire-fighting agents.

Product is compatible with standard fire-fighting agents.

Further information : Fire residues and contaminated fire extinguishing water must

be disposed of in accordance with local regulations.

Valvoline	Page: 5
SAFETY DATA SHEET	Revision Date: 01/15/2018
	Print Date: 1/16/2018
	SDS Number: R0296766
Zerex™ G-05 AntIfreeze	Version: 1.5
377726	

Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

Special protective equipment

for firefighters

: In the event of fire, wear self-contained breathing apparatus.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

: Use personal protective equipment.

Ensure adequate ventilation.

Persons not wearing protective equipment should be excluded

from area of spill until clean-up has been completed.

Environmental precautions

: Prevent product from entering drains.

Prevent further leakage or spillage if safe to do so.

If the product contaminates rivers and lakes or drains inform

respective authorities.

Methods and materials for containment and cleaning up

: Soak up with inert absorbent material (e.g. sand, silica gel,

acid binder, universal binder, sawdust).

Keep in suitable, closed containers for disposal.

Other information : Comply with all applicable federal, state, and local regulations.

SECTION 7. HANDLING AND STORAGE

Advice on safe handling : Do not breathe vapours/dust.

Do not smoke.

Container hazardous when empty.

Avoid exposure - obtain special instructions before use.

Avoid contact with skin and eyes.

Smoking, eating and drinking should be prohibited in the

application area.

For personal protection see section 8.

Dispose of rinse water in accordance with local and national

regulations.

Conditions for safe storage

: Keep container tightly closed in a dry and well-ventilated

place.

Containers which are opened must be carefully resealed and

kept upright to prevent leakage. Observe label precautions.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Valvoline.	Page: 6
SAFETY DATA SHEET	Revision Date: 01/15/2018
	Print Date: 1/16/2018
	SDS Number: R0296766
Zerex™ G-05 AntIfreeze	Version: 1.5
377726	

Components with workplace control parameters

Components	CAS-No.	Value type	Control	Basis
		(Form of	parameters /	
		exposure)	Permissible	
			concentration	
ETHYLENE GLYCOL	107-21-1	С	100 mg/m3	ACGIH
			Aerosol only	
		С	50 ppm	OSHA P0
			125 mg/m3	
		С	40 ppm	CAL PEL
			100 mg/m3	
			Vapour	
DIETHYLENE GLYCOL	111-46-6	TWA	10 mg/m3	US WEEL
DISODIUM TETRABORATE	1330-43-4	TWA	1 mg/m3	NIOSH REL
ANHYDROUS				
		PEL	5 mg/m3	CAL PEL
		TWA	10 mg/m3	OSHA P0
		TWA	2 mg/m3	ACGIH
			Inhalable fraction	
			(Borate)	
		STEL	6 mg/m3	ACGIH
			Inhalable fraction	
			(Borate)	

Hazardous components without workplace control parameters

Components	CAS-No.
SODIUM BENZOATE	532-32-1

Engineering measures

: Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below exposure guidelines (if applicable) or below levels that cause known, suspected or apparent adverse effects.

Personal protective equipment

Respiratory protection

A NIOSH-approved air-purifying respirator with an appropriate cartridge and/or filter may be permissible under certain circumstances where airborne concentrations are expected to exceed exposure limits (if applicable) or if overexposure has otherwise been determined. Protection provided by air-purifying respirators is limited. Use a positive pressure, air-supplied respirator if there is any potential for uncontrolled release, exposure levels are not known or any other circumstances where an air-purifying respirator may not provide adequate protection.

In the case of vapour formation use a respirator with an approved filter.

Hand protection

Remarks : The suitability for a specific workplace should be discussed

Valvoline	Page: 7
SAFETY DATA SHEET	Revision Date: 01/15/2018
	Print Date: 1/16/2018
	SDS Number: R0296766
Zerex™ G-05 AntIfreeze	Version: 1.5
377726	

with the producers of the protective gloves.

Eye protection : Not required under normal conditions of use. Wear splash-

proof safety goggles if material could be misted or splashed

into eyes.

Skin and body protection : Wear as appropriate:

Impervious clothing

Safety shoes

Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Wear resistant gloves (consult your safety equipment

supplier).

Hygiene measures : Wash hands before breaks and at the end of workday.

When using do not eat or drink. When using do not smoke.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state : liquid

Colour : light yellow

Odour : mild

Odour Threshold : No data available

pH : Average 6.5

Melting point/freezing point : No data available

Boiling point/boiling range : 330 °F / 166 °C

(1013 hPa)

Flash point : $> 250.0 \,^{\circ}\text{F} / > 121.1 \,^{\circ}\text{C}$

Method: closed cup

Evaporation rate : > 1

Ethyl Ether

Flammability (solid, gas) : No data available

Upper explosion limit : 15.3 %(V)

Lower explosion limit : 3.2 %(V)

Vapour pressure : 1.1 mmHg (20 °C)

Valvoline	Page: 8
SAFETY DATA SHEET	Revision Date: 01/15/2018
	Print Date: 1/16/2018
	SDS Number: R0296766
Zerex™ G-05 AntIfreeze	Version: 1.5
377726	

Relative vapour density : > 1AIR=1

Relative density : No data available

Density : Average 1.1362 g/cm3 (15.56 °C)

Solubility(ies)

Water solubility : No data available

Solubility in other solvents : No data available

Partition coefficient: n-

octanol/water

: No data available

Thermal decomposition : No data available

Viscosity

Viscosity, dynamic : No data available

Viscosity, kinematic : No data available

Oxidizing properties : No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity : No decomposition if stored and applied as directed.

Chemical stability : Stable under recommended storage conditions.

Possibility of hazardous

reactions

: Product will not undergo hazardous polymerization.

Conditions to avoid : excessive heat

Exposure to moisture

Incompatible materials : Acids

Aldehydes Alkali metals

Alkaline earth metals

Bases iron salts strong alkalis

Strong oxidizing agents Sulphur compounds

Hazardous decomposition

products

Alcohols Aldehydes

Valvoline	Page: 9
SAFETY DATA SHEET	Revision Date: 01/15/2018
	Print Date: 1/16/2018
	SDS Number: R0296766
Zerex™ G-05 AntIfreeze	Version: 1.5
377726	

carbon dioxide and carbon monoxide

ethers

Hydrocarbons Organic acids Sodium oxides toxic fumes ketones

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of

exposure

: Inhalation Skin contact

Eye Contact Ingestion

Acute toxicity

Harmful if swallowed.

Product:

Acute oral toxicity

Remarks: Ingestion of medications contaminated with diethylene glycol has caused kidney failure and death in humans. Products containing diethylene glycol should be

considered toxic by ingestion.

Acute dermal toxicity : Remarks: Skin absorption of this material (or a component)

may be increased through injured skin.

Components:

ETHYLENE GLYCOL:

Acute oral toxicity : LD0 (Human): Estimated 1.56 g/kg

Assessment: The component/mixture is classified as acute

oral toxicity, category 4.

Acute inhalation toxicity : LC50 (Rat): 10.9 mg/l

Exposure time: 1 h

Test atmosphere: dust/mist

Assessment: No adverse effect has been observed in acute

inhalation toxicity tests.

Acute dermal toxicity : LD50 (Rabbit): 9,530 mg/kg

Acute toxicity (other routes of

administration)

: LD50 (Rat): 5,010 mg/kg

Application Route: Intraperitoneal

DIETHYLENE GLYCOL:

Acute oral toxicity : LD50 (Human): Expected 1,120 mg/kg

Valvoline.	Page: 10
SAFETY DATA SHEET	Revision Date: 01/15/2018
	Print Date: 1/16/2018
	SDS Number: R0296766
Zerex™ G-05 AntIfreeze	Version: 1.5
377726	

Target Organs: Kidney

Acute inhalation toxicity : LC50 (Rat): > 4.6 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

Assessment: No adverse effect has been observed in acute

inhalation toxicity tests.

Acute dermal toxicity : LD50 (Rabbit): 13,300 mg/kg

SODIUM BENZOATE:

Acute oral toxicity : LD50 (Rat, male and female): 3,450 mg/kg

: LC50 (Rat): > 12.2 mg/l Acute inhalation toxicity

Exposure time: 4 h

Test atmosphere: dust/mist

Remarks: Information given is based on data obtained from

similar substances.

DISODIUM TETRABORATE ANHYDROUS:

Acute inhalation toxicity : LC50 (Rat): > 2.03 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

Method: OECD Test Guideline 403

Assessment: No adverse effect has been observed in acute

inhalation toxicity tests.

Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg

Assessment: No adverse effect has been observed in acute

dermal toxicity tests.

Skin corrosion/irritation

Not classified based on available information.

Components:

ETHYLENE GLYCOL: Species: Rabbit

Result: No skin irritation

DIETHYLENE GLYCOL:

Species: Human

Result: Slight, transient irritation

SODIUM BENZOATE:

Result: Slight, transient irritation

DISODIUM TETRABORATE ANHYDROUS:

Species: Rabbit

Result: No skin irritation

Valvoline	Page: 11
SAFETY DATA SHEET	Revision Date: 01/15/2018
	Print Date: 1/16/2018
	SDS Number: R0296766
Zerex™ G-05 AntIfreeze	Version: 1.5
377726	

Serious eye damage/eye irritation

Not classified based on available information.

Product:

Remarks: Unlikely to cause eye irritation or injury.

Components:

ETHYLENE GLYCOL:

Result: Slight, transient irritation

DIETHYLENE GLYCOL:

Species: Rabbit

Result: Slight, transient irritation

SODIUM BENZOATE:

Species: Rabbit

Result: Irritating to eyes.

Method: OECD Test Guideline 405

DISODIUM TETRABORATE ANHYDROUS:

Result: Slight, transient irritation

Respiratory or skin sensitisation

Skin sensitisation: Not classified based on available information. Respiratory sensitisation: Not classified based on available information.

Components:

ETHYLENE GLYCOL:

Test Type: Maximisation Test

Species: Guinea pig

Assessment: Does not cause skin sensitisation.

DIETHYLENE GLYCOL: Test Type: Maximisation Test

Species: Guinea pig

Method: Directive 67/548/EEC, Annex V, B.6.

Result: Did not cause sensitisation on laboratory animals.

DISODIUM TETRABORATE ANHYDROUS:

Test Type: Buehler Test Species: Guinea pig

Assessment: Does not cause skin sensitisation.

Method: OECD Test Guideline 406

Germ cell mutagenicity

Not classified based on available information.

Components:

ETHYLENE GLYCOL:

Genotoxicity in vitro : Test Type: Ames test

Test species: Salmonella typhimurium

Metabolic activation: with and without metabolic activation

Valvoline	Page: 12
SAFETY DATA SHEET	Revision Date: 01/15/2018
	Print Date: 1/16/2018
	SDS Number: R0296766
Zerex™ G-05 AntIfreeze	Version: 1.5
377726	

Result: negative

DIETHYLENE GLYCOL:

Genotoxicity in vitro Test Type: Ames test

Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 471

Result: negative

GLP: yes

Test species: Chinese hamster ovary cells

Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 479

Result: negative

GLP: yes

: Test Type: In vivo micronucleus test Genotoxicity in vivo

Test species: Mouse

Method: OECD Test Guideline 474

Result: negative

GLP: yes

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

May damage fertility or the unborn child.

Components:

DISODIUM TETRABORATE ANHYDROUS:

Reproductive toxicity -: Clear evidence of adverse effects on sexual function and Assessment fertility, and/or on development, based on animal experiments

STOT - single exposure

Not classified based on available information.

STOT - repeated exposure

Not classified based on available information.

Components:

ETHYLENE GLYCOL: Exposure routes: Ingestion Target Organs: Kidney, Liver

Assessment: May cause damage to organs through prolonged or repeated exposure.

DIETHYLENE GLYCOL: Exposure routes: Ingestion

Target Organs: Kidney

Assessment: May cause damage to organs through prolonged or repeated exposure.

Aspiration toxicity

Not classified based on available information.

Product:

No aspiration toxicity classification

Experience with human exposure

Valvoline.	Page: 13
SAFETY DATA SHEET	Revision Date: 01/15/2018
	Print Date: 1/16/2018
	SDS Number: R0296766
Zerex™ G-05 AntIfreeze	Version: 1.5
377726	

Components:

DIETHYLENE GLYCOL:

Liver

Further information

Product:

Remarks: No data available

Carcinogenicity:

IARC Group 2A: Probably carcinogenic to humans

SODIUM NITRITE 7632-00-0

SODIUM NITRATE 7631-99-4

OSHA No component of this product present at levels greater than or

equal to 0.1% is identified as a carcinogen or potential

carcinogen by OSHA.

NTP No component of this product present at levels greater than or

equal to 0.1% is identified as a known or anticipated carcinogen

by NTP.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Product:

Ecotoxicology Assessment

Acute aquatic toxicity : Acute aquatic toxicity Category 3; Harmful to aquatic life.

Chronic aquatic toxicity : Not classified based on available information.

Components:

ETHYLENE GLYCOL:

Toxicity to fish : LC50 (Lepomis macrochirus (Bluegill sunfish)): 27,540 mg/l

Exposure time: 96 h Test Type: static test

LC50 (Pimephales promelas (fathead minnow)): 8,050 mg/l

Exposure time: 96 h

Toxicity to daphnia and other

aquatic invertebrates

: LC50 (Daphnia magna (Water flea)): > 10,000 mg/l

Exposure time: 48 h Test Type: static test

Toxicity to algae : EC50 (Pseudokirchneriella subcapitata (green algae)): 6,500 -

13,000 mg/l

End point: Growth inhibition Exposure time: 7 Days

Valvoline		Page: 14
SAFETY DATA SHEET	Rev	rision Date: 01/15/2018
		Print Date: 1/16/2018
	S	DS Number: R0296766
Zerex™ G-05 AntIfreeze		Version: 1.5
377726		

Toxicity to fish (Chronic

toxicity)

: NOEC (Pimephales promelas (fathead minnow)): 32,000 mg/l

Exposure time: 7 d

Toxicity to daphnia and other

aquatic invertebrates (Chronic toxicity)

: NOEC (Daphnia magna (Water flea)): 24,000 mg/l

Exposure time: 7 d

DIETHYLENE GLYCOL:

Toxicity to daphnia and other

aquatic invertebrates

: LC50 (Water flea (Daphnia magna)): > 10,000 mg/l

Exposure time: 24 h Test Type: static test Method: DIN 38412

SODIUM BENZOATE:

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): > 100 mg/l

Exposure time: 96 h Test Type: static test Method: Static Remarks: Mortality

Toxicity to daphnia and other

aquatic invertebrates

: LC50 (Water flea (Daphnia magna)): > 100 mg/l

Exposure time: 96 h Test Type: static test Method: Static Remarks: Mortality

DISODIUM TETRABORATE ANHYDROUS:

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 79.7 mg/l

Exposure time: 96 h

Remarks: Information refers to the main component.

Toxicity to algae : NOEC (Pseudokirchneriella subcapitata (green algae)): 17.5

mg/l

End point: Growth inhibition Exposure time: 72 h Test Type: static test

Method: OECD Test Guideline 201

Remarks: Information refers to the main component.

Toxicity to fish (Chronic

toxicity)

: NOEC (Danio rerio (zebra fish)): 5.6 mg/l

Exposure time: 34 d Test Type: semi-static test

Method: OECD Test Guideline 210

Remarks: Information refers to the main component.

Persistence and degradability Components:

ETHYLENE GLYCOL:

Biodegradability : Result: Readily biodegradable.

Biodegradation: 90 - 100 %

Exposure time: 10 d

Valvoline	Page: 15
SAFETY DATA SHEET	Revision Date: 01/15/2018
	Print Date: 1/16/2018
	SDS Number: R0296766
Zerex™ G-05 AntIfreeze	Version: 1.5
377726	

Method: OECD Test Guideline 301

DIETHYLENE GLYCOL:

Biodegradability : Result: Readily biodegradable. Biodegradation: 70 - 80 %

Exposure time: 28 d

Method: OECD Test Guideline 301B

SODIUM BENZOATE:

Biodegradability : Result: Readily biodegradable.

Biodegradation: 88 % Exposure time: 28 d

Method: OECD Test Guideline 301

DISODIUM TETRABORATE ANHYDROUS:

Biodegradability : Result: The methods for determining biodegradability are not

applicable to inorganic substances.

No data available

Bioaccumulative potential

Components:

ETHYLENE GLYCOL:

Bioaccumulation : Species: Crayfish (Procambarus)

Bioconcentration factor (BCF): 0.27

Exposure time: 61 d Concentration: 1000 mg/l Method: Flow through

Partition coefficient: n-

octanol/water

: log Pow: -1.36

DIETHYLENE GLYCOL:

Bioaccumulation : Species: Leuciscus idus (Golden orfe)

Bioconcentration factor (BCF): 100

Partition coefficient: n-

octanol/water

: log Pow: -1.47

No data available
Mobility in soil
Components:
No data available
Other adverse effects
No data available

Product:

Additional ecological

information

: An environmental hazard cannot be excluded in the event of unprofessional handling or disposal., Harmful to aquatic life.

Components:

SECTION 13. DISPOSAL CONSIDERATIONS

Valvoline .	Page: 16
SAFETY DATA SHEET	Revision Date: 01/15/2018
	Print Date: 1/16/2018
	SDS Number: R0296766
Zerex™ G-05 AntIfreeze	Version: 1.5
377726	

Disposal methods

General advice : The product should not be allowed to enter drains, water

courses or the soil.

Do not contaminate ponds, waterways or ditches with

chemical or used container.

Send to a licensed waste management company.

Dispose of in accordance with all applicable local, state and

federal regulations.

Contaminated packaging : Empty remaining contents.

Dispose of as unused product.

Empty containers should be taken to an approved waste

handling site for recycling or disposal. Do not re-use empty containers.

SECTION 14. TRANSPORT INFORMATION

International transport regulations

REGULATION

,					
ID NUMBER	PROPER SHIPPING NAME	*HAZARD CLASS	SUBSIDIARY HAZARDS	PACKING GROUP	MARINE POLLUTANT /
					LTD. QTY.

U.S. DOT - ROAD

Not dangerous goods	

CFR_RAIL_C

	Not dangerous goods

U.S. DOT - INLAND WATERWAYS

Not dangerous goods	

TDG_ROAD_C

Not dangerous goods

TDG_RAIL_C

Not dangerous goods	

TDG INWT C

Not dangerous goods

Valvoline.	Page: 17
SAFETY DATA SHEET	Revision Date: 01/15/2018
	Print Date: 1/16/2018
	SDS Number: R0296766
Zerex™ G-05 AntIfreeze	Version: 1.5
377726	

INTERNATIONAL MARITIME DANGEROUS GOODS

Not dangerous goods	

INTERNATIONAL AIR TRANSPORT ASSOCIATION - CARGO

Not dangerous goods

INTERNATIONAL AIR TRANSPORT ASSOCIATION - PASSENGER

Not dangerous goods

MX DG

Not dangerous goods	5

*ORM = ORM-D, CBL = COMBUSTIBLE LIQUID

Marine pollutant	no

Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

SECTION 15. REGULATORY INFORMATION

EPCRA - Emergency Planning and Community Right-to-Know Act CERCLA Reportable Quantity

Components	CAS-No.	Component RQ	Calculated product RQ
		(lbs)	(lbs)
ETHYLENE GLYCOL	107-21-1	5000	5315

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 311/312 Hazards : Acute Health Hazard

Chronic Health Hazard

SARA 313

ETHYLENE GLYCOL 107-21-1 94.07 %

California Prop 65 WARNING: This product contains a chemical known to the

State of California to cause birth defects or other reproductive

harm.

ETHYLENE GLYCOL 107-21-1

The components of this product are reported in the following inventories:

Valvoline.	Page: 18
SAFETY DATA SHEET	Revision Date: 01/15/2018
	Print Date: 1/16/2018
	SDS Number: R0296766
Zerex™ G-05 AntIfreeze	Version: 1.5
377726	

DSL : All components of this product are on the Canadian DSL

AICS : On the inventory, or in compliance with the inventory

ENCS : Not in compliance with the inventory

KECI : Not in compliance with the inventory

PICCS : Not in compliance with the inventory

IECSC : On the inventory, or in compliance with the inventory

TSCA : On TSCA Inventory


Inventories

AICS (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TCSI (Taiwan), TSCA (USA)

SECTION 16. OTHER INFORMATION

Further information

Revision Date: 01/15/2018



NFPA Flammable and Combustible Liquids Classification

Combustible Liquid Class IIIB

Full text of H-Statements

H302 Harmful if swallowed.

H319 Causes serious eye irritation.

H360 May damage fertility or the unborn child.

H373 May cause damage to organs through prolonged or repeated exposure

if swallowed.

Valvoline	Page: 19
SAFETY DATA SHEET	Revision Date: 01/15/2018
	Print Date: 1/16/2018
	SDS Number: R0296766
Zerex™ G-05 AntIfreeze	Version: 1.5
377726	

Sources of key data used to compile the Safety Data Sheet Valvoline internal data including own and sponsored test reports The UNECE administers regional agreements implementing harmonised classification for labelling (GHS) and transport.

The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances. This SDS has been prepared by Valvoline's Environmental Health and Safety Department (1-800-VALVOLINE).

List of abbreviations and acronyms that could be, but not necessarily are, used in this safety data

ACGIH: American Conference of Industrial Hygienists

BEI: Biological Exposure Index

CAS: Chemical Abstracts Service (Division of the American Chemical Society).

CMR: Carcinogenic, Mutagenic or Toxic for Reproduction

FG: Food grade

GHS: Globally Harmonized System of Classification and Labeling of Chemicals.

H-statement : Hazard Statement

IATA: International Air Transport Association.

IATA-DGR: Dangerous Goods Regulation by the "International Air Transport Association" (IATA).

ICAO: International Civil Aviation Organization

ICAO-TI (ICAO): Technical Instructions by the "International Civil Aviation Organization"

IMDG: International Maritime Code for Dangerous Goods

ISO: International Organization for Standardization

logPow: octanol-water partition coefficient

LCxx: Lethal Concentration, for xx percent of test population

LDxx: Lethal Dose, for xx percent of test population. ICxx: Inhibitory Concentration for xx of a substance

Ecxx: Effective Concentration of xx N.O.S.: Not Otherwise Specified

OECD: Organization for Economic Co-operation and Development

OEL: Occupational Exposure Limit P-Statement: Precautionary Statement PBT: Persistent, Bioaccumulative and Toxic

PPE: Personal Protective Equipment STEL: Short-term exposure limit STOT: Specific Target Organ Toxicity

TLV: Threshold Limit Value TWA: Time-weighted average

vPvB: Very Persistent and Very Bioaccumulative

WEL: Workplace Exposure Level

CERCLA: Comprehensive Environmental Response, Compensation, and Liability Act

Valvoline	Page: 20
SAFETY DATA SHEET	Revision Date: 01/15/2018
	Print Date: 1/16/2018
	SDS Number: R0296766
Zerex™ G-05 AntIfreeze	Version: 1.5
377726	

DOT : Department of Transportation

FIFRA: Federal Insecticide, Fungicide, and Rodenticide Act HMIRC: Hazardous Materials Information Review Commission

HMIS : Hazardous Materials Identification System

NFPA: National Fire Protection Association

NIOSH: National Institute for Occupational Safety and Health OSHA: Occupational Safety and Health Administration

PMRA: Health Canada Pest Management Regulatory Agency

RTK: Right to Know

WHMIS: Workplace Hazardous Materials Information System