SAFETY DATA SHEET



Section 1: IDENTIFICATION

Product Name: Concrete Masonry Products (Pigmented)

Generic ID: Concrete Masonry Units, Segmental Retaining Walls

Usage and Restrictions: Concrete masonry units are used in the construction of residential and commercial struc-

tures as part of a building's envelope and interior walls, and can be used in load-bearing or veneer applications. Segmental retaining wall units are used as a means to retain earth

slopes in residential and commercial projects.

Supplier Details: York Building Products

950 Smile Way York, PA 17404

Emergency Phone #: 717.848.2831

Section 2:

HAZARD(S) IDENTIFICATION

GHS Classification: Carcinogenicity: 1A

Eye Irritation: 2A Repeated Exposure Skin Irritation: 2 Specific Target Organ Toxicity: 2

GHS Label Elements:





Signal Word: Danger

Hazard Statements: Sawing or grinding may result in release of dust particles which may (acute:) cause minor

irritation of the eye or nose. (chronic:) result in lung disease (silicosis) if exposed to excessive

amounts for prolonged periods.

Prevention: Wear NIOSH-approved respirator and tight fitting foggles when sawing or grinding.

Response: If exposed or concerned: Get medical advice/attention. If on skin: Wash with plenty of water.

Take off contaminated clothing and wash it before reuse. If in eyes: Rinse continuously with

water for several minutes. Remove contact lenses, if present and easy to do.

Storage: Store product pallets on stable ground. Do not double-stack pallets.

Disposal: Dispose of contents/container in accordance with local/regional/national/international

regulations.

Hazards Not Otherwise Classified: None known.



Section 3:

COMPOSITION / INFORMATION ON INGREDIENTS

Ingredient(s)	UN Number	CAS Number	% (by weight)
Course aggregate	Not available.	Not available.	15 - 60
Portland cement	Not available.	65997-15-1	9 - 31
Ashes/residues	Not available.	68131-74-8	0.1 - 30
Water	Not available.	7732-18-5	10 - 30
Silica, Quartz, Crystalline	Not available.	14808-60-7	3 - 7
Ferric oxide	UN1376	1309-37-1	1 - 5
Calcium carbonate	Not available.	1317-65-3	1 - 5
Calcium hydroxide	Not available.	1305-62-0	1 - 5
Silica, amorphous, fumed	Not available.	7631-86-9	1 - 5
Admixtures	Not available.	Not available.	0.1 - 1

Section 4:	FIRST AID MEASURES
------------	--------------------

Description of Necessary First Aid Measures:

Eye Contact: Immediately flush with plenty of water for at least 15 minutes. Hold eyelids apart. Remove

contacts if present and easy to do. Beyond flushing, do not attempt to remove material

from the eye(s). Get medical attention if irritation develops or persists.

Inhalation: Move to fresh air. Call a physician if symptoms develop or persist.

Skin Contact: Wash off with soap and water. Get medical attention if irritation develops and persists.

Ingestion: Rinse mouth and drink plenty of water. Never give anything by mouth to an unconscious

person. Get medical attention.

Most Important Symptoms & Effects, Both Acute and Delayed:

Inhaling dust may cause discomfort in the chest, shortness of breath, and coughing. Prolonged inhalation may cause chronic health effects. This product contains crystalline silica. Prolonged or repeated inhalation of respirable crystalline silica liberated from this product can cause silicosis, and may cause cancer.

Indication of Immediate Medical Attention and Special Treatment Needed, If Necessary:

Eye Contact: Causes serious eye irritation. Symptoms may include discomfort or pain, excess blinking

and tear production, with possible redness and swelling.

Inhalation: Dust may cause respiratory tract irritation.

Skin Contact: Causes skin irritation. Wear gloves when handling product to avoid drying and mechanical

abrasion of the skin. May cause sensitization by skin contact.

Ingestion: Not a normal route of exposure. May result in obstruction and temporary irritation of the

digestive tract.



Section 5:

FIRE-FIGHTING MEASURES

Extinguishing Media:

Suitable Extinguishing Media: Treat for surrounding material.

Unsuitable Extinguishing Media: Not available.

Special Protective Equipment For

Fire-Fighters:

Use protective equipment appropriate for surrounding materials. No specific precautions.

Section 6:

ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment and Emergency Procedures:

Wear appropriate protective equipment and clothing during clean-up of materials that contain or may release dust.

Methods and Materials For Containment and Cleaning-Up

Spilled material, where dust is generated, may overexpose cleanup personnel to respirable crystalline silica-containing dust. Do not dry sweep or use compressed air for clean-up. Wetting of spilled material and/or use of respiratory protective equipment may be necessary. Avoid discharge of fine particulate matter into drains.

Section 7:

HANDLING AND STORAGE

Precautions for Safe Handling:

Handling: Avoid contact with skin and eyes. Good housekeeping is key to prevent accumulation of

dust. Avoid generating and breathing dust. Use wet methods, if appropriate, to reduce the generation of dust. The use of compressed air for cleaning clothing, equipment, etc, is not

recommended. Handle with care. When using do not eat or drink. (See section 8)

General Hygiene Advice: Launder contaminated clothing before reuse. Wash hands before eating or drinking.

Conditions For Safe Storage, Including Any Incompatibilities: Avoid dust buildup by frequent cleaning and suitable construction of the storage area.



Section 8:

EXPOSURE CONTROLS AND PERSONAL MEASURES

Control Parameters

Occupational exposure limits:

- 1 Value equivalent to OSHA formulas (29 CFR 1910.1000; 29 CFR 1917; 29 CFR 1918)
- 2 Value also applies to MSHA metal/Non-Metal (1973 TLVs at 30 CFR 56/57.5001)
- 3 OSHA enforces 0.250 mg/m³ in construction and shipyards (CPL-03-00-007)
- 4 Value also applies to OSHA construction (29 CRF 1926.55 Appendix A) and shipyards (29 CFR 1915.1000 Table Z)
- 5 MSHA limit = 10 mg/m³

Occupational Exposure Limits		
<u>Ingredient</u>	OSHA-PEL	ACGIH-TLV
Coarse aggregate	Not available.	Not available.
Portland cement	15 mg/m³ (total); 5 mg/m³ (resp)	1 mg/m³ (<1% crystalline silica, respirable fraction)
Ashes (residues)	Not available.	Not available.
Silica, crystalline, quartz	((10 mg/m3)/(%SiO2+2) (resp))	
	((30 mg/m3)/(%SiO2+2) (total))	
	((250)/(%SiO2+5) mppcf (resp))	0.025 mg/m ³
Ferric oxide	10 mg/m ³	5 mg/m³ (iron oxide fume;
		dust as Fe)
Calcium carbonate	15 mg/m³ (total); 5 mg/m³ (resp)	10 mg/m³
Calcium hydroxide	15 mg/m³ (total); 5 mg/m³ (resp)	5 mg/m ³
Silica, amorphous	80 mg/m ³ /%SiO2	10 mg/m ³
Admixtures	Not available.	Not available.

Engineering Controls: When using product, provide local and general exhaust ventilation to keep airborne dust

concentrations below exposure limits. Use wet methods, if appropriate, to reduce the gen-

eration of dust.

Exposure Guidelines: OSHA PELs, MSHA PELs, and ACGIH TLVs are 8-hr TWA values. NIOSH RELs are for TWA ex-

posures up to 10-hr/day and 40-hr/wk. Occupational exposure to nuisance dust (total and

respirable) and respirable crystalline silica should be monitored and controlled.

Individual Protection Measures:

Hygiene Measures: Observe good hygiene, such as washing after handling the material and before eating and

drinking. Routinely wash work clothing and protective equipment.

Eye/Face Protection: Wear safety glasses with side shields (or goggles).

Hand/Body Protection: Use personal protective equipment as required.

Hand/Body Protection: When performing work that produces dust or respirable crystalline silica in excess of

applicable exposure limits, wear a NIOSH-approved respirator that is properly fitted and is in good condition. Respirators must be used in accordance with all applicable workplace

regulations.



Section 9:

PHYSICAL AND CHEMICAL PROPERTIES

Appearance: Appearance: Fully cured and hydrated concrete.

Color: Not available. Varies.

Odor: Odorless.

Odor Threshold: Not applicable.

Physical State: Solid.

pH: Not applicable. Melting/Freezing Point: Not applicable. **Boiling Point:** Not applicable. Flash Point: Not applicable. **Evaporation Rate:** Not applicable. Flammability: Not flammable. Lower Flammability/Explosive Limit: Not applicable. Upper Flammability/Explosive Limit: Not applicable. Vapor Pressure: Not applicable. Vapor Density: Not applicable. Relative Density/Specific Gravity: Not applicable. Solubility: Insoluble. Partition coefficient: n-octanol/water: Not applicable. **Auto-ignition Temperature:** Not applicable.

Auto-ignition Temperature:

Decomposition Temperature:

Viscosity:

SADT:

Oxidizing Properties:

Explosive Properties:

Not applicable.

Not applicable.

Not applicable.

Not applicable.

Not applicable.

Section 10:

STABILITY AND REACTIVITY

Reactivity: Product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical Stability: Material is stable under normal conditions.

Hazardous Reaction Possibility: No dangerous reaction known under conditions of normal use.

Conditions to avoid: None known.

Incompatible materials: None known.

Hazardous decomposition: None known.



Section 11:

TOXICOLOGICAL INFORMATION

Information On Toxicological Effects:

Acute Toxicity: Not expected to be acutely toxic.

Irritation/Corrosion: Skin: Causes skin irritation. Wear gloves when handling product to avoid drying and mechani-

cal abrasion of the skin. May cause sensitization by skin contact.

Eyes: Causes serious eye irritation. Symptoms may include discomfort or pain, excess blinking

and tear production, with possible redness and swelling.

Ingestion: Not likely due to product form. However accidental ingestion may cause discomfort.

Inhalation: Dust may cause respiratory tract irritation.

Sensitization: Respiratory sensitization: No respiratory sensitizing effects known.

Skin sensitization: Not known to be a dermal irritant or sensitizer.

Mutagenicity: No data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Aspiration Hazard: Not expected to be an aspiration hazard.

Reproductive Toxicity: Not expected to be a reproductive hazard.

Symptoms: Dust: discomfort in the chest. Shortness of breath. Coughing.

Carcinogenicity: Respirable crystalline silica has been classified by IARC and NTP as a known human carcinogen,

and classified by ACGIH as a suspected human carcinogen.

Acute Toxicity:

Ingredient IDLH LC50 LD50

Coarse aggregateNot available.Not available.Not available.Portland cement5000 mg/m3Not available.Not available.

Ashes (residues) Not available. Not available. Oral > 2000 mg/kg, rat Water Not available. Inhalation 90000 Oral > 90000 mg/kg, rat mg/m³/4h, rat Dermal > 90000 mg/kg, rabbit

Silica, crystalline, quartz Ca [25 mg/m3 (cristobalite, Not available. Oral 500 mg/kg, rat

tridymite); 50 mg/m3

(quartz, tripoli)]

Ferric oxide 2500 mg Fe /m3 Not available. Oral >10000 mg/kg, rat Calcium carbonate Not available. Not available. Oral 6450 mg/kg, rat Not available. Not available. Calcium hydroxide Oral 7340 mg/kg, rat Silica, amorphous Not available. Inhalation Oral >5000 mg/kg, rat

≥58.8 mg/l/1h, rat Dermal >2000 mg/kg, rabbit

Admixtures Not available. Not available. Not available.



Section 12:

ECOLOGICAL INFORMATION

Ecotoxicity: No ecological consideration when used according to directions.

Persistence and degradability: Not applicable. Bioaccumulative potential: Not applicable. Mobility in soil: Not applicable.

Other adverse effects: No other adverse environmental effects (e.g., ozone depletion, photochemical ozone

creation potential, global warming potential) are expected from this component.

Section 13:

DISPOSAL CONSIDERATIONS

Disposal Methods: Do not allow fine particulate matter to drain into sewers/water supplies. Do not contaminate

ponds, waterways or ditches with fine particulates. Dispose of contents in accordance with

local/regional/national/international regulations.

Hazardous Waste Code: Not regulated.

Waste From Residues/Unused

Products:

Dispose of in accordance with local regulations. Empty containers or liners may retain some

product residues. This material and its container must be disposed of in a safe manner.

Section 14:

TRANSPORTATION INFORMATION

	DOT Classification	<u>TDG</u>	NOM-004-SCT2-1994
UN Number	Not regulated.	Not regulated.	Not regulated.
UN Proper Shipping Name	Not applicable.	Not applicable.	Not applicable.
Transport Hazard Class(es)	Not applicable.	Not applicable.	Not applicable.
Packing Group	Not applicable.	Not applicable.	Not applicable.
Environmental Hazards	Not available.		

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code: Not available.



Section 15:

REGULATORY INFORMATION

Safety, Health and Environmental Regulations/ Legislations Specific For The Chemical:

US: SDS prepared pursuant to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

SARA Title III				
Ingredient	Section 302	Section 304	CERCLA	Section
	(EHS) TPQ (lbs.)	EHS RQ (lbs.)	RQ (lbs.)	313
Coarse aggregate	Not listed.	Not listed.	Not listed.	Not listed.
Portland cement	Not listed.	Not listed.	Not listed.	Not listed.
Ashes (residues)	Not listed.	Not listed.	Not listed.	Not listed.
Water	Not listed.	Not listed.	Not listed.	Not listed.
Silica, crystalline, quartz	Not listed.	Not listed.	Not listed.	Not listed.
Ferric oxide	Not listed.	Not listed.	Not listed.	Not listed.
Calcium carbonate	Not listed.	Not listed.	Not listed.	Not listed.
Calcium hydroxide	Not listed.	Not listed.	Not listed.	Not listed.
Silica, amorphous	Not listed.	Not listed.	Not listed.	Not listed.
Admixtures	Not listed.	Not listed.	Not listed.	Not listed.

SOURCE AGENCY CARCINOGEN CLASSIFICATIONS:

CP65 California Proposition 65

OSHA (O) Occupational Safety and Health Administration.

ACGIH (G) American Conference of Governmental Industrial Hygienists. A1 - Confirmed human carcinogen. A2 - Suspected human

carcinogen. A3 - Animal carcinogen. A4 - Not classifiable as a human carcinogen. A5 - Not suspected as a human carcinogen. International Agency for Research on Cancer. 1 - The agent (mixture) is carcinogenic to humans. 2A - The agent (mixture) is

IARC (I) International Agency for Research on Cancer. 1 - The agent (mixture) is carcinogenic to humans. 2A - The agent (mixture) is probably carcinogenic to humans; there is limited evidence of carcinogenicity in humans and sufficient evidence of carcinogenicity in experimental animals. 2B - The agent (mixture) is possibly carcinogenic to humans; there is limited evidence of

genicity in experimental animals. 2B - The agent (mixture) is possibly carcinogenic to humans; there is limited evidence of carcinogenicity in humans in the absence of sufficient evidence of carcinogenicity in experimental animals. 3 - The agent (mixture, exposure circumstance) is not classifiable as to its carcinogenicity to humans. 4 - The agent (mixture, exposure

circumstance) is probably not carcinogenic to humans.

NTP (N) National Toxicology Program. 1 - Known to be carcinogens. 2 - Reasonably anticipated to be carcinogens.

Section 16:

OTHER INFORMATION

Date of Preparation: 05-30-15
Expiration Date: None
Version: 1.0
Revision Date: N/A

Disclaimer: We believe the statements, technical information and recommendations contained herein are reliable, but are given without warranty or guarantee of any kind. In particular, the data furnished in this sheet do not address hazards that may be posed by other materials mixed with limestone to produce limestone products. Users should review other relevant material safety data sheets before working with this limestone or working on limestone products. Inexperienced product users should obtain proper training before using this product. It is the user's responsibility to satisfy oneself as to the suitability and completeness of this information for the user's own particular use.